

# Streetscape Protector

Larsen Streetscape Protector is an advanced water-based impregnating sealer and surface protector. It is manufactured from advanced fluoropolymers to reduce water, oil and dirt absorption. Unlike other products, the appearance of the impregnated surface remains almost totally unchanged.

- **Advanced fluoropolymer based protector suitable for all porous surfaces and all types of natural stone**
- **Does not affect the appearance of the impregnated surface**
- **Protects against water based staining**
- **Protects against oil based staining**
- **Reduces dirt pick-up**
- **Water-based impregnator**

## DIRECTIONS:

### Preparation

The substrate should be dry, clean and thoroughly sound and free from oils, grease, dust, loose particles or any other contaminants. The surface should be free from dirt or staining. Any existing stains will be almost impossible to remove following treatment.

Any residues of grout material should be fully removed. This is often best achieved by washing the surface with a mild acidic cleaning product and then rinsing thoroughly.

Streetscape Protector is best applied to a surface which has been cleaned, rinsed and allowed to dry.



### Mixing

Supplied ready for use. Do not further dilute.

Mix the contents of the container before application.

### Application

Apply under dry frost free weather conditions.

The surface to be treated must be clean and dry. Streetscape Protector is an impregnating sealer and requires a dry surface to ensure adequate impregnation.

Apply by brush, roller or low pressure spray. It is often best to apply two light coats rather than one heavy coat.

### Restrictions

Always test an inconspicuous area first to ensure suitability for use, particularly on polished surfaces.

Apply under dry frost free weather conditions.

**HANDLING PRECAUTION** Larsen products are generally safe provided they are used as instructed and that certain precautions normally taken when handling chemicals are observed eg, do not allow any material to come into contact with foodstuffs. Avoid contact with skin. Do not swallow. Always read the safety information on the pack and the Safety Data Sheet before use.

**IMPORTANT NOTE** The information given in this data sheet is based on both current development work and many years' field experience. Whilst every effort is made to ensure that the information is reliable we cannot accept responsibility for any work carried out with our materials where we have no control over methods of application, site conditions etc.

**For further information consult our Technical Department**  
**TEL: 02890774000 Online: [www.larsenbuildingproducts.com](http://www.larsenbuildingproducts.com)**

## Technical Information

PRODUCT INFORMATION	
FORM	Liquid
COLOUR(S)	Clear Straw (dries colourless)
HAZARD INFORMATION	IRRITANT – Consult Safety Datasheet before use
CLEANING	Clean tools, equipment etc. using warm water. Mechanical means are necessary when the product has set.
PACKAGING	5L and 25L Containers
STORAGE CONDITIONS	Store in sealed containers in dry conditions, protected from extremes of temperature
SHELF LIFE	12 months in unopened manufacturer's packaging
APPLICATION INFORMATION	
APPLICATION TEMPERATURE	+5°C to +30°C
DRRYING TIME	Approx. 60 minutes
TIME TO TRAFFIC	Light Foot Traffic - after 12 hours Vehicle Traffic - after 1 day (depending on site conditions)
COVERAGE	25 L will cover approx. 125m <sup>2</sup> depending on porosity and texture of surface

**HANDLING PRECAUTION** Larsen products are generally safe provided they are used as instructed and that certain precautions normally taken when handling chemicals are observed eg. do not allow any material to come into contact with foodstuffs. Avoid contact with skin. Do not swallow. Always read the safety information on the pack and the Safety Data Sheet before use.

**IMPORTANT NOTE** The information given in this data sheet is based on both current development work and many years' field experience. Whilst every effort is made to ensure that the information is reliable we cannot accept responsibility for any work carried out with our materials where we have no control over methods of application, site conditions etc.

**For further information consult our Technical Department**  
**TEL: 02890774000 Online: [www.larsenbuildingproducts.com](http://www.larsenbuildingproducts.com)**

TDS - Streetscape Protector