

DECLARATION OF PERFORMANCE

in accordance with Annex III of the Construction Products Regulation (EU) No 305/2011

No. DOP-934-001


1. *Unique identification code of the product-type:*
Chemcrete ME2
2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*
Batch number: see packaging of the product
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
Air entraining/plasticizing admixture for masonry mortar
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*
**Larsen Manufacturing Ltd t/a Larsen Building Products
4 West Bank Road
Harbour Industrial Estate
Belfast
BT3 9JL**
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
not relevant
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
System 2+
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*
The notified body SGS UK Ltd, identification number CE0120, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: a certificate of conformity of the factory production control - Certificate no. GB13/89172.
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*
not relevant

9. Declared performance

Essential characteristics	Performance	Harmonised Technical specification
Chloride ion content	Max 0.1% by mass	EN 934-3:2009 +A1:2012
Alkali content	Max 1.5% by mass	
Corrosion behaviour	Contains components only from EN 934-1:2008, Annex A.1 Approved list	
Compressive strength	At 28 days: Test mix ≥ 70 % of control mix	
Entrained Air	T2 (1) Total-air content A_1 after standard mixing $A_1 = (17 \pm 3)$ % by volume	
	T2 (2) Air content after 1h standing $\geq A_1 - 3\%$ by volume	
	T2 (3) Air content after extended mixing $\leq A_1 + 5\%$ by volume and $\geq A_1 - 5\%$ by volume	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Tim Moore
Chief Chemist



Place & Date of Issue