

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

Multigrout 60

Revision 4

Revision date 2017-08-23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Multigrout 60
---------------------	---------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC5] Industrial use resulting in inclusion into or onto a matrix; [AC4] Stone, plaster, cement, glass and ceramic articles;
--------------------	---

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36/37/38 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes, respiratory system and skin.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; Acute Tox. 4: H332; STOT SE 3: H335; STOT RE 2: H373;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. Acute Tox. 4: H332 - Harmful if inhaled. STOT SE 3: H335 - May cause respiratory irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Multigrout 60

Revision 4

Revision date 2017-08-23

2.2. Label elements

Precautionary Statement: Response	P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ . P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Portland Cement		65997-15-1	266-043-4		50 - 60%	Xi; R36/37/38	
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4		30 - 40%		
Aluminium Powder (Aluminium metal)	013-002-00-1	7429-90-5	231-072-3		0 - 0.5%	F; R11-15	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Portland Cement		65997-15-1	266-043-4		50 - 60%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;	
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4		30 - 40%	Acute Tox. 4: H332; STOT RE 2: H373;	

Description

	This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life. Contact with wet cement may give rise to burns or ulceration.
--	---

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

Multigrout 60

Revision 4
Revision date 2017-08-23

5.1. Extinguishing media

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid raising dust. Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Multigrout 60

Revision 4

Revision date 2017-08-23

8.1.1. Exposure Limit Values

Aluminium Powder (Aluminium metal)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: 10 WEL 8-hr limit mg/m3 total respirable dust: 4	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Multigrout 60 (Multigrout)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Portland Cement	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: 10 WEL 8-hr limit mg/m3 total respirable dust: 4	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Silica Sand (<1% Respirable Quartz)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: 10 WEL 8-hr limit mg/m3 total respirable dust: 4	WEL 8-hr limit mg/m3: 0.1 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear: Suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Grey
Solubility	Slightly soluble in water

9.2. Other information

Bulk Density	1.6 g/cm ³
--------------	-----------------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Not determined.	
Skin corrosion/irritation	Irritating to eyes, respiratory system and skin.

Multigrout 60

Revision 4

Revision date 2017-08-23

11.1. Information on toxicological effects

Respiratory or skin sensitisation	Contains chromium VI. May produce an allergic reaction.
-----------------------------------	---

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

Further information

	No known adverse environmental effects.
--	---

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 12 - 12.1. Toxicity.
Text of risk phrases in Section 3	R11 - Highly flammable. R15 - Contact with water liberates extremely flammable gases. R36/37/38 - Irritating to eyes, respiratory system and skin.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation. Acute Tox. 4: H332 - Harmful if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--