

CREOCOAT



Creocoat is an oil-based wood stain for protecting and decorating fences, sheds and other domestic, external timber products. Creocoat is compatible with all Larsen Wood Preservatives.



OIL-BASED WOOD STAIN
WATER REPELLENT
READY TO USE
EASY TO APPLY

TECHNICAL INFORMATION:

PRODUCT INFORMATION	
FORM:	Oily Liquid
COLOUR:	Dark Brown
ODOUR:	Mild Tar
SPECIFIC GRAVITY:	0.99 g/ml
FLASH POINT:	85°C
COVERAGE:	1L will cover 4-6 m ² (depending on timber)

DIRECTIONS FOR USE:

PREPARATION

Surfaces must be clean, dry, and free from dust and grease. For best results, apply to dry timber.

APPLICATION

Ready to use - do not dilute. Brush or spray apply. Alternatively a dip tank system may be used.

CAUTION

For External Use ONLY. Ensure adequate ventilation during application and curing. Avoid naked flames – flammable. No smoking or eating during application. Consult Safety Data Sheet before use. If in doubt, contact our Technical Department.

CLEANING

Clean tools, equipment, etc. using white spirit or proprietary brush cleaner.

STORAGE

Creocoat should be stored in closed containers protected from extremes of temperature. Part used packs may develop a skin on storage.

SHELF LIFE

12 months in unopened manufacturer's containers.

PACKAGING

4L, 20L and 200L packs.