

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

Aluminium Reflective Paint

Revision 1

Revision date 2017-08-30

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Aluminium Reflective Paint
--------------	----------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
-------------	--

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	T; R45-46 Xn; R65 Xi; R36/37/38 R52/53 Symbols: T: Toxic.
Main hazards	Irritating to eyes, respiratory system and skin. May cause cancer. May cause heritable genetic damage. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.
2.1.2. Classification - EC 1272/2008	Asp. Tox. 1: H304; Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335; Muta. 1B: H340; Carc. 1B: H350; Aquatic Chronic 3: H412;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H335 - May cause respiratory irritation. Muta. 1B: H340 - May cause genetic defects . Carc. 1B: H350 - May cause cancer .

Aluminium Reflective Paint

Revision 1

Revision date 2017-08-30

2.2. Label elements

Precautionary Statement: Prevention	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
Precautionary Statement: Disposal	P405 - Store locked up. P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Low boiling point hydrogen treated naphtha - naphtha (petroleum), hydrodesulfurized heavy	649-330-00-2	64742-82-1	265-185-4			Carc. Cat. 2; R45 Muta. Cat. 2; R46 Xn; R65	
1,2,4-Trimethylbenzene	601-043-00-3	95-63-6	202-436-9			R10 Xn; R20 Xi; R36/37/38 N; R51/53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Low boiling point hydrogen treated naphtha - naphtha (petroleum), hydrodesulfurized heavy	649-330-00-2	64742-82-1	265-185-4			Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304;	
1,2,4-Trimethylbenzene	601-043-00-3	95-63-6	202-436-9			Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Toxic by inhalation. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Toxic in contact with skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention.
Ingestion	Toxic if swallowed. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. If swallowed, seek medical advice immediately and show this container or

Aluminium Reflective Paint

Revision 1
Revision date 2017-08-30

4.1. Description of first aid measures

label. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use as appropriate: Carbon dioxide (CO₂), Dry chemical, Foam.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear: Self-contained breathing apparatus. Wear chemical protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

1,2,4-Trimethylbenzene	DIR: 2000/39	8hTWA ppm: 20
	8hTWA mg/m ³ : 100	STEL ppm: -
	STEL mg/m ³ : -	NOT: -

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Aluminium Reflective Paint

Revision 1
Revision date 2017-08-30

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Silver
Odour	Characteristic

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	No data is available on this product.
----------------	---------------------------------------

SECTION 12: Ecological information


SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Hazard pictograms

	
--	---

14.1. UN number

	UN1999
--	--------

14.2. UN proper shipping name

	TARS, LIQUID
--	--------------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

Aluminium Reflective Paint

Revision 1

Revision date 2017-08-30

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Text of risk phrases in Section 3	R10 - Flammable R20 - Harmful by inhalation. R36/37/38 - Irritating to eyes, respiratory system and skin. R45 - May cause cancer. R46 - May cause heritable genetic damage. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed.
Text of Hazard Statements in Section 3	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Muta. 1B: H340 - May cause genetic defects . Carc. 1B: H350 - May cause cancer . Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H332 - Harmful if inhaled. STOT SE 3: H335 - May cause respiratory irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--