

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

Bltumen Primer

Revision 3

Revision date 2017-08-09

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Bltumen Primer
--------------	----------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	<p>[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [SU19] Building and construction work; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [ERC5] Industrial use resulting in inclusion into or onto a matrix;</p> <p>-----</p> <p>[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [SU19] Building and construction work; [PC9a] Coatings and paints, thinners, paint removers; [PROC7] Industrial spraying; [ERC5] Industrial use resulting in inclusion into or onto a matrix;</p>
-------------	--

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xn; R65 Symbols: Xn: Harmful.
Main hazards	Harmful: may cause lung damage if swallowed.
2.1.2. Classification - EC 1272/2008	Asp. Tox. 1: H304;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P331 - Do NOT induce vomiting.

Bitumen Primer

Revision 3

Revision date 2017-08-09

2.2. Label elements

Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	649-405-00-X	64742-88-7	265-191-7			Xn; R65	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	649-405-00-X	64742-88-7	265-191-7			Asp. Tox. 1: H304;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best
--	---

Bitumen Primer

Revision 3
Revision date 2017-08-09

7.1. Precautions for safe handling

Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Black
Odour	Characteristic

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1999

14.2. UN proper shipping name

TARS, LIQUID

Bitumen Primer

Revision 3

Revision date 2017-08-09

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Text of risk phrases in Section 3	R65 - Harmful: may cause lung damage if swallowed.
Text of Hazard Statements in Section 3	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--