

# SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

## 3:1 Tanking Mix

Revision 2

Revision date 2017-08-30

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

<b>Product name</b>	3:1 Tanking Mix
---------------------	-----------------

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Product Use</b>	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC5] Industrial use resulting in inclusion into or onto a matrix; [AC4] Stone, plaster, cement, glass and ceramic articles;
--------------------	---

#### 1.3. Details of the supplier of the safety data sheet


<b>Company</b>	Larsen Building Products Ltd
<b>Address</b>	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
<b>Web</b>	www.larsenbuildingproducts.com
<b>Telephone</b>	+44 (0)28 9077 4000
<b>Fax</b>	+44 (0)28 9077 6945
<b>Email</b>	t.moore@larsenbuildingproducts.com

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

<b>2.1.1. Classification - 1999/45/EC</b>	Xi; R36/37/38 Symbols: Xi: Irritant.
<b>Main hazards</b>	Irritating to eyes, respiratory system and skin.
<b>2.1.2. Classification - EC 1272/2008</b>	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;

#### 2.2. Label elements

<b>Hazard pictograms</b>	
<b>Signal Word</b>	Danger
<b>Precautionary Statement: Prevention</b>	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
<b>Precautionary Statement: Response</b>	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

## 3:1 Tanking Mix

Revision 2

Revision date 2017-08-30

## 2.2. Label elements

<b>Precautionary Statement:</b> <b>Storage</b> <b>Precautionary Statement:</b> <b>Disposal</b>	lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER/doctor/ . P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up.
	P501 - Dispose of contents/container to

## 2.3. Other hazards

<b>Other hazards</b>	P13 - Contains chromium (VI). May produce an allergic reaction. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
----------------------	---

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Portland Cement		65997-15-1	266-043-4		20 - 30%	Xi; R36/37/38	

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Portland Cement		65997-15-1	266-043-4		20 - 30%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;	

## Description

	This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.
--	---

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

<b>Inhalation</b>	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
<b>Eye contact</b>	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
<b>Skin contact</b>	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
<b>Ingestion</b>	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Carbon oxides.
--	----------------

## 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

## 5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

# 3:1 Tanking Mix

Revision 2

Revision date 2017-08-30

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid raising dust. Ensure adequate ventilation of the working area. Wear suitable protective equipment.

### 6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

### 6.3. Methods and material for containment and cleaning up

Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Exposure Limit Values

Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

### 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear: Suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Grey

## SECTION 10: Stability and reactivity

### 10.2. Chemical stability

Stable under normal conditions.

## SECTION 11: Toxicological information

### 11.1.4. Toxicological Information

## 3:1 Tanking Mix

Revision 2

Revision date 2017-08-30

## 11.1.4. Toxicological Information

No data available

## SECTION 12: Ecological information

## 12.1. Toxicity

No data available

## SECTION 13: Disposal considerations

## General information

Dispose of in compliance with all local and national regulations.

## SECTION 14: Transport information

## Further information

The product is not classified as dangerous for carriage.

## SECTION 15: Regulatory information

## SECTION 16: Other information

## Other information

## Text of risk phrases in Section 3

R36/37/38 - Irritating to eyes, respiratory system and skin.

## Text of Hazard Statements in Section 3

Skin Irrit. 2: H315 - Causes skin irritation.  
 Skin Sens. 1: H317 - May cause an allergic skin reaction.  
 Eye Dam. 1: H318 - Causes serious eye damage.  
 STOT SE 3: H335 - May cause respiratory irritation.

## Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.