

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

Larpruf CG

Revision 2

Revision date 2017-08-23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Larpruf CG
---------------------	------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC5] Industrial use resulting in inclusion into or onto a matrix; [AC4] Stone, plaster, cement, glass and ceramic articles;
--------------------	---

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36/37/38 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes, respiratory system and skin.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; Acute Tox. 4: H332; STOT SE 3: H335; STOT RE 2: H373;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. Acute Tox. 4: H332 - Harmful if inhaled. STOT SE 3: H335 - May cause respiratory irritation. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Larpruf CG

Revision 2

Revision date 2017-08-23

2.2. Label elements

Precautionary Statement: Response	P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ . P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Portland Cement		65997-15-1	266-043-4		50 - 60%	Xi; R36/37/38	
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4		30 - 40%		
Sodium carbonate	011-005-00-2	497-19-8	207-838-8		10 - 20%	Xi; R36	
Tartaric Acid		87-69-4	201-766-0		1 - 10%	Xi; R36/37/38	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Portland Cement		65997-15-1	266-043-4		50 - 60%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;	
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4		30 - 40%	Acute Tox. 4: H332; STOT RE 2: H373;	
Sodium carbonate	011-005-00-2	497-19-8	207-838-8		10 - 20%	Eye Irrit. 2: H319;	
Tartaric Acid		87-69-4	201-766-0		1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335;	
Silica Flour		14808-60-7			1 - 10%	STOT RE 2: H373;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

Larpruf CG

Revision 2
Revision date 2017-08-23

5.1. Extinguishing media

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Avoid raising dust. Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Silica Sand (<1% Respirable Quartz)	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 0.1
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).

Larpruf CG

Revision 2
Revision date 2017-08-23

8.2. Exposure controls

Respiratory protection	Wear: Suitable respiratory equipment.
------------------------	---------------------------------------

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Grey

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

SECTION 16: Other information

Larpruf CG

Revision 2

Revision date 2017-08-23

Other information

Revision	This document differs from the previous version in the following areas: 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 12 - 12.1. Toxicity.
Text of risk phrases in Section 3	R36/37/38 - Irritating to eyes, respiratory system and skin. R36 - Irritating to eyes.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation. Acute Tox. 4: H332 - Harmful if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Eye Irrit. 2: H319 - Causes serious eye irritation.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--