

DECLARATION OF PERFORMANCE

in accordance with Annex III of the Construction Products Regulation (EU) No 305/2011

No. DOP-998-001

1. *Unique identification code of the product-type:*
Larsen Building Mortar
2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*
Batch number: see packaging or delivery docket
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
Prescribed general purpose masonry mortar for moderate exposure
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*
**Larsen Manufacturing Ltd t/a Larsen Building Products
4 West Bank Road
Harbour Industrial Estate
Belfast
BT3 9JL**
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
not relevant
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
System 4
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*
EN998-2:2010
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*
not relevant


9. Declared performance

Essential characteristics	Performance	Harmonised Technical specification
Reaction to Fire	A1	EN 998-2:2010
Water Absorption	NPD	
Water Vapour Diffusion coefficient	$\mu = 15/35$ (tabulated value)	
Thermal Conductivity	$\lambda_{10,dry} = 0.61W/mK$ (tabulated value P=50%)	
Proportion of Constituents	By Weight : Portland Cement (42.5N) 13.5% Aggregates 86.5% Air Entraining Agent 0.02%	
Durability	For use in moderate exposure (as per EN998-2 National Annex NA)	
Dangerous Substances	See MSDS	


This mortar conforms to BS EN 998-2:2010 - Prescribed general purpose masonry mortar for moderate exposure

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Tim Moore
Chief Chemist



Belfast