

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

Larpruf B6

Revision 1
Revision date 2017-08-21

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Larpruf B6
--------------	------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC4] Use in batch and other process (synthesis) where opportunity for exposure arises; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
-------------	--

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36/38 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes and skin.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Eye Irrit. 2: H319;

2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation.
Precautionary Statement: Prevention	P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Larpruf B6

Revision 1
Revision date 2017-08-21

2.2. Label elements

P321 - Specific treatment (see on this label).
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Diethylene glycol (2,2'-Oxydiethanol)	603-140-00-6	111-46-6	203-872-2		0 - 0.5%	Xn; R22	
Tallow Oleine					1 - 10%	Xi; R36/38	
Potassium hydroxide	019-002-00-8	1310-58-3	215-181-3		1 - 10%	Xn; R22 C; R35	
N-Methyldiethanolamine	603-079-00-5	105-59-9	203-312-7		1 - 10%	Xi; R36	
Formaldehyde...% (Formaldehyde)	605-001-00-5	50-00-0	200-001-8		0 - 0.5%	Carc. Cat. 3; R40 T; R23/24/25 C; R34 R43	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Tallow Oleine					1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	
Potassium hydroxide	019-002-00-8	1310-58-3	215-181-3		1 - 10%	Acute Tox. 4: H302; Skin Corr. 1A: H314;	
N-Methyldiethanolamine	603-079-00-5	105-59-9	203-312-7		1 - 10%	Eye Irrit. 2: H319;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Larpruf B6

Revision 1

Revision date 2017-08-21

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Diethylene glycol (2,2'-Oxydiethanol)	WEL 8-hr limit ppm: 23	WEL 8-hr limit mg/m3: 101
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Formaldehyde...% (Formaldehyde)	WEL 8-hr limit ppm: 2	WEL 8-hr limit mg/m3: 2.5
	WEL 15 min limit ppm: 2	WEL 15 min limit mg/m3: 2.5
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Potassium hydroxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear: Suitable respiratory equipment.

SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

Larpruf B6

Revision 1

Revision date 2017-08-21

SECTION 11: Toxicological information

11.1.4. Toxicological Information

N-Methyldiethanolamine	Oral Rat LD50: 1945mg/kg	Dermal Rabbit LD50: 5990ul/kg
------------------------	--------------------------	-------------------------------

SECTION 12: Ecological information**SECTION 13: Disposal considerations**

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information**SECTION 16: Other information**

Other information

Revision	This document differs from the previous version in the following areas: 12 - 12.1. Toxicity.
Text of risk phrases in Section 3	R22 - Harmful if swallowed. R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed. R34 - Causes burns. R35 - Causes severe burns. R36/38 - Irritating to eyes and skin. R36 - Irritating to eyes. R40 - Limited evidence of a carcinogenic effect. R43 - May cause sensitisation by skin contact.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H302 - Harmful if swallowed. Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.