

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

Primer Grip 360

Revision 6
Revision date 2017-08-09

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Primer Grip 360
---------------------	-----------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [ERC8c] Wide dispersive indoor use resulting in inclusion into or onto a matrix; [AC4] Stone, plaster, cement, glass and ceramic articles;
--------------------	---

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Main hazards	No Significant Hazard
---------------------	-----------------------

2.2. Label elements

Risk phrases	No Significant Hazard
---------------------	-----------------------

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

Primer Grip 360

Revision 6

Revision date 2017-08-09

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

8.2.1. Appropriate engineering controls

	Ensure adequate ventilation of the working area.
--	--

8.2.2. Individual protection measures

	Wear protective clothing.
--	---------------------------

Eye / face protection

	In case of splashing, wear:.. Approved safety goggles.
--	--

Skin protection - Handprotection

	Chemical resistant gloves (PVC).
--	----------------------------------

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	pink/Green
Odour	Characteristic
pH	6 - 8
Freezing Point	0 °C
Initial boiling point	100 °C
Flammability (solid, gas)	N/A
Relative density	1.0 - 1.1
Solubility	Miscible in water

9.2. Other information

Specific gravity	1 - 1.1 g/cm ³
-------------------------	---------------------------

Primer Grip 360

Revision 6

Revision date 2017-08-09

Water solubility

Miscible in water.

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

14.1. UN number

The product is not classified as dangerous for carriage.

14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

14.4. Packing group

The product is not classified as dangerous for carriage.

14.5. Environmental hazards

The product is not classified as dangerous for carriage.

14.6. Special precautions for user

The product is not classified as dangerous for carriage.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information**SECTION 16: Other information**

Other information

Product Subcategory

Binding primers - 30 g/l.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and

Primer Grip 360

Revision 6

Revision date 2017-08-09

Further information

	belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--
