

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

Chemcrete LSR

Revision 5
Revision date 2019-10-10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Chemcrete LSR
---------------------	---------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [SU19] Building and construction work; [PC0] Other; [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact); [ERC3] Formulation in materials;
--------------------	--

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Acute Tox. 4: H302; Acute Tox. 4: H312; Acute Tox. 4: H332; STOT SE 1: H370;
---	--

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H312 - Harmful in contact with skin. Acute Tox. 4: H332 - Harmful if inhaled. STOT SE 1: H370 - Causes damage to organs .
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P270 - Do no eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Chemcrete LSR

Revision 5
Revision date 2019-10-10

2.2. Label elements

Precautionary Statement: Response	P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell. P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P330 - Rinse mouth.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Hydrochloric acid...%	017-002-01-X		231-595-7			Skin Corr. 1B: H314; STOT SE 3: H335;
Methanol	603-001-00-X	67-56-1	200-659-6			Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370;
Sucrose		57-50-1	200-334-9			
Mono ethylene glycol (Ethane-1,2-diol particulate)	603-027-00-1	107-21-1	203-473-3			Acute Tox. 4: H302;
Lactic Acid		79-33-4				

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Treat as for inhalation if any signs of poisoning are present. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. Seek medical attention.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Alcohol resistant foam. Carbon oxides.
--	--

5.2. Special hazards arising from the substance or mixture

	. Very toxic. Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear:. Self-contained breathing apparatus. Wear chemical protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	--

Chemcrete LSR

Revision 5

Revision date 2019-10-10

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Keep away from sources of ignition - No smoking. Use explosion proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Methanol	WEL 8-hr limit ppm:	200	WEL 8-hr limit mg/m3:	266
	WEL 15 min limit ppm:	250	WEL 15 min limit mg/m3:	333
	WEL 8-hr limit mg/m3 total inhalable dust:	-	WEL 15 min limit mg/m3 total inhalable dust:	-
	WEL 8-hr limit mg/m3 total respirable dust:	-	WEL 15 min limit mg/m3 total respirable dust:	-
Mono ethylene glycol (Ethane-1,2-diol particulate)	WEL 8-hr limit ppm:	-	WEL 8-hr limit mg/m3:	10
	WEL 15 min limit ppm:	-	WEL 15 min limit mg/m3:	-
	WEL 8-hr limit mg/m3 total inhalable dust:	-	WEL 15 min limit mg/m3 total inhalable dust:	-
	WEL 8-hr limit mg/m3 total respirable dust:	-	WEL 15 min limit mg/m3 total respirable dust:	-
Mono ethylene glycol (Ethane-1,2-diol vapour)	WEL 8-hr limit ppm:	20	WEL 8-hr limit mg/m3:	52
	WEL 15 min limit ppm:	40	WEL 15 min limit mg/m3:	104
	WEL 8-hr limit mg/m3 total inhalable dust:	-	WEL 15 min limit mg/m3 total inhalable dust:	-
	WEL 8-hr limit mg/m3 total respirable dust:	-	WEL 15 min limit mg/m3 total respirable dust:	-
Sucrose	WEL 8-hr limit ppm:	-	WEL 8-hr limit mg/m3:	10
	WEL 15 min limit ppm:	-	WEL 15 min limit mg/m3:	20
	WEL 8-hr limit mg/m3 total inhalable dust:	-	WEL 15 min limit mg/m3 total inhalable dust:	-
	WEL 8-hr limit mg/m3 total respirable dust:	-	WEL 15 min limit mg/m3 total respirable dust:	-

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment.

Chemcrete LSR

Revision 5

Revision date 2019-10-10

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless to straw yellow
Odour	Characteristic

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Toxic by inhalation, in contact with skin and if swallowed.
----------------	---

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Hazard pictograms

--	--

14.1. UN number

	UN1230
--	--------

14.2. UN proper shipping name

	METHANOL
--	----------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	6.1
IMDG	3
Subsidiary risk	6.1
IATA	3
Subsidiary risk	6.1

14.4. Packing group

Chemcrete LSR

Revision 5
Revision date 2019-10-10

14.4. Packing group

Packing group	II
---------------	----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	336
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-D
----------	---------

IATA

Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	352
Maximum quantity	1 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 2 - 2.1.2. Classification - EC 1272/2008. 2 - Precautionary Statement: Response.
Text of Hazard Statements in Section 3	Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H335 - May cause respiratory irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin. Acute Tox. 3: H331 - Toxic if inhaled. STOT SE 1: H370 - Causes damage to organs . STOT SE 2: H371 - May cause damage to organs . Acute Tox. 4: H302 - Harmful if swallowed.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--