

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

Larseal Impregnation Part B

Revision 5

Revision date 2019-12-16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Larseal Impregnation Part B
---------------------	-----------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact); [ERC3] Formulation in materials;
--------------------	---

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Eye Dam. 1: H318; Acute Tox. 4: H332;
---	--

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Eye Dam. 1: H318 - Causes serious eye damage. Acute Tox. 4: H332 - Harmful if inhaled.
Precautionary Statement: Prevention	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Larseal Impregnation Part B

Revision 5
Revision date 2019-12-16

2.2. Label elements

P310 - Immediately call a POISON CENTER/doctor/ .
 P312 - Call a POISON CENTER/doctor/ /if you feel unwell.
 P321 - Specific treatment (see on this label).
 P332+P313 - If skin irritation occurs: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7			Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;
Butan-1-ol	603-004-00-6	71-36-3	200-751-6			Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336;
1-Methoxy-2-propanol (1-Methoxypropan-2-ol)	603-064-00-3	107-98-2	203-539-1			Flam. Liq. 3: H226; STOT SE 3: H336;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.

5.2. Special hazards arising from the substance or mixture

. Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

Larseal Impregnation Part B

Revision 5
Revision date 2019-12-16

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

1-Methoxy-2-propanol (1-Methoxypropan-2-ol)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 375
	WEL 15 min limit ppm: 150	WEL 15 min limit mg/m3: 560
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -
Butan-1-ol	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 154
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless to straw yellow
Odour	Characteristic

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

Larseal Impregnation Part B

Revision 5
Revision date 2019-12-16

10.4. Conditions to avoid

Heat, sparks and open flames.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1307

14.2. UN proper shipping name

XYLENES

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code F-E S-D

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L

Larseal Impregnation Part B

Revision 5
Revision date 2019-12-16

IATA

Maximum quantity	60 L
------------------	------

SECTION 15: Regulatory information**SECTION 16: Other information**

Other information

Text of Hazard Statements in Section 3	Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Acute Tox. 4: H332 - Harmful if inhaled. Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
--	--

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--