

# KITCHEN & BATH SILICONE



Larsen Kitchen & Bathroom Silicone is a one part low modulus elastic sealant based on acetoxy curing polysiloxanes. After application Kitchen & Bath cures with atmospheric moisture to provide a durable, waterproof elastic seal with excellent adhesion to glass, ceramics, enamel and porcelain. It is ideal for waterproof sealing in bathrooms and kitchens, around baths, showers, tiles and sanitary ware.



**SANITARY SILICONE SEALANT**  
**CONTAINS FUNGICIDE**  
**LOW MODULUS**  
**USE IN BATHROOMS AND SHOWERS**  
**SEAL KITCHEN UNITS**

**TECHNICAL INFORMATION:**

PRODUCT INFORMATION									
<b>FORM:</b>	Paste								
<b>STANDARD COLOUR(S):</b>	Clear, White, Cream								
<b>MATERIAL:</b>	Acetoxy curing silicone sealant								
<b>HAZARD INFORMATION:</b>	Generally non-hazardous in normal use - consult safety datasheet before use								
<b>CLEANING:</b>	Clean tools, equipment etc. using white spirit. Mechanical means are necessary when the product has set.								
<b>PACKAGING:</b>	Standard Silicone Cartridge								
<b>STORAGE CONDITIONS:</b>	Store in sealed containers in dry conditions, protected from extremes of temperature								
<b>SHELF LIFE:</b>	12 months in unopened manufacturer's packaging								
APPLICATION INFORMATION									
<b>SPECIFIC GRAVITY:</b>	0.94 g/ml								
<b>MOVEMENT:</b>	+/-25%								
<b>SKINNING TIME:</b>	5 - 10 min @ 20°C								
<b>APPLICATION TEMP.:</b>	+ 5 to + 30°C								
<b>TEMP. RESISTANCE:</b>	-50 to + 120°C								
<b>HARDNESS SHORE A:</b>	10								
<b>100% MODULUS:</b>	0.15 MPa								
<b>ELONGATION AT BREAK:</b>	800%								
<b>MINIMUM JOINT WIDTH:</b>	4 mm								
<b>MAXIMUM JOINT WIDTH:</b>	25 mm								
<b>COVERAGE:</b>	<table border="0"> <thead> <tr> <th>Joint</th> <th>Linear Metres / Cartridge</th> </tr> </thead> <tbody> <tr> <td>5x5mm</td> <td>11</td> </tr> <tr> <td>10x10mm</td> <td>3</td> </tr> <tr> <td>10x20mm</td> <td>1.5</td> </tr> </tbody> </table>	Joint	Linear Metres / Cartridge	5x5mm	11	10x10mm	3	10x20mm	1.5
Joint	Linear Metres / Cartridge								
5x5mm	11								
10x10mm	3								
10x20mm	1.5								

## **DIRECTIONS FOR USE:**

### **PREPARATION**

Surfaces to be sealed must be clean, dry, sound and free from dust, oil or grease.

### **PRIMING**

The following surfaces do not need primer: glass, ceramic or enamel.

### **APPLICATION**

Remove cartridge tip with a sharp knife and cut nozzle to required size and angle.

Using skeleton gun, apply sealant continuously, ensuring full contact with all surfaces.

Joint must be tooled within five minutes. Soapy water will assist finishing process.

### **RESTIRCTIONS**

Current best practice and trade body recommendations should be followed. Cannot be overpainted. Always carry out trials to ensure compatibility of substrate. Not recommended for aquaria, on concrete, marble, lead, copper, galvanized steel and not for PE, PP, Teflon and bituminous or wax containing surfaces. Not recommended for direct contact with the perimeter of isolation glass and the edges of laminated safety glass. Adhesion tests prior to application are recommended. It is the user's responsibility to determine suitability.