

POLYFLOOR



Polyfloor is an economical, single pack, high gloss, oil-based floor paint based on tough polyurethane resins to give a tough, durable finish. Polyfloor is suitable for use in areas subject to light to medium traffic. Applications include workshops, domestic garages, general storage areas, corridors, etc.



COLOURED, SINGLE PACK SYSTEM
LOW COST MAINTENANCE PRODUCT
READY TO USE
EASY TO APPLY
LONG SHELF LIFE WHEN STORED CORRECTLY

TECHNICAL INFORMATION:

PRODUCT INFORMATION	
FORM:	Thick bodied paint
COLOURS:	Red, Dark Grey, Light Grey
HAZARD INFORMATION:	Flammable - Consult Safety Datasheet before use
CLEANING:	Clean tools, equipment, etc. using white spirit or thinners. Mechanical means are necessary when the product has set.
PACKAGING:	5L Metal Paint tins
STORAGE CONDITIONS:	Store in sealed containers in dry conditions, protected from extremes of temperature, protect form frost.
SHELF LIFE:	12 months in unopened manufacturer's packaging
APPLICATION INFORMATION	
APPLICATION TEMPERATURE:	+5°C to +30°C
SPECIFIC GRAVITY:	1.10 g/ml
VOLUME SOLIDS:	45.0% v/v
VOC:	<500g/L
DRYING TIME:	Touch dry in 2-3 hours Overcoat after 24-48 hours
TIME TO TRAFFIC:	Light Foot Traffic - after 12-24 hours Full Traffic - after 1-3 days (depending on site conditions)
COVERAGE:	10 - 12 m ² /L per coat depending on porosity and texture of surface

DIRECTIONS FOR USE:

PREPARATION

All surfaces should be at least 14 days old. It is recommended that surfaces should be mechanically prepared. Surfaces should be clean, firm and free from contamination such as grease, dirt, oil, etc. Standard good painting practices should be employed.

PRIMING

Polyfloor can be used as a self-priming coating where, according to surface porosity, up to 10% (max.) white spirit may be added to the first coat.

APPLICATION

Standard paint application techniques are used with Larsen Polyfloor. On porous substrates it is advisable to use a priming coat. Two coats (excluding prime coat) are required to achieve maximum depth of colour and ensure maximum protection. In some cases, 3 coats may be required (e.g. light colours). Subsequent coats are applied in accordance with the overcoating recommendations given above.

RESTRICTIONS

Do not apply in thick layers. Polyfloor is not suitable for areas where chemical spillage may occur. Ensure adequate ventilation during application and curing. Avoid naked flames - flammable. Do not apply to wet surfaces, in conditions of high humidity or when rain is forecast. Protect from rain until dry. No smoking during application. If in doubt, contact our Technical Department. In areas of wear, the surface sheen will dull and may give a whitish appearance.