

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

Larcote PE Pt A

Revision 4

Revision date 2017-09-20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Larcote PE Pt A
--------------	-----------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC10] Roller application or brushing; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
-------------	---

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	T; R45 Xi; R36/38-43 N; R51/53 Symbols: T: Toxic. N: Dangerous for the environment.
Main hazards	Irritating to eyes and skin. May cause sensitisation by skin contact. May cause cancer. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Carc. 1B: H350; STOT RE 2: H373; Aquatic Chronic 2: H411;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Carc. 1B: H350 - May cause cancer . STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood.

Larcote PE Pt A

Revision 4

Revision date 2017-09-20

2.2. Label elements

Precautionary Statement: Response	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P391 - Collect spillage.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Pitch residue - pitch, coal tar, low-temperature	648-069-00-1	90669-57-1	292-651-4			Carc. Cat. 2; R45	
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5			Xi; R36/38 R43 N; R51/53	
Talc (Talc, respirable dust)		14807-96-6					
Silicon Dioxide		69012-64-2	273-761-1				

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Pitch residue - pitch, coal tar, low-temperature	648-069-00-1	90669-57-1	292-651-4			Carc. 1B: H350;	
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5			Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411; STOT RE 2: H373;	
Silica Flour		14808-60-7					
Talc (Talc, respirable dust)		14807-96-6				Carc. 1B: H350i;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Toxic by inhalation. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Toxic in contact with skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention.
Ingestion	Toxic if swallowed. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. If swallowed, seek medical advice immediately and show this container or label. DO NOT INDUCE VOMITING.

Larcote PE Pt A

Revision 4

Revision date 2017-09-20

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear: Self-contained breathing apparatus. Wear chemical protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

Silicon Dioxide	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3:
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total inhalable dust: 6	WEL 15 min limit mg/m3 total inhalable dust:
	WEL 8-hr limit mg/m3 total respirable dust: 0.3	WEL 15 min limit mg/m3 total respirable dust:
Talc (Talc, respirable dust)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 1
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -

8.2. Exposure controls**8.2.1. Appropriate engineering controls**

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

Larcote PE Pt A

Revision 4
Revision date 2017-09-20

8.2. Exposure controls

Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
------------------------	---

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Black
Odour	Characteristic

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	May cause cancer.
----------------	-------------------

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.


SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Hazard pictograms

	
--	---

14.1. UN number

	UN1999
--	--------

14.2. UN proper shipping name

	TARS, LIQUID
--	--------------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

Larcote PE Pt A

Revision 4

Revision date 2017-09-20

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 14 - ADR/RID. 14 - IMDG. 14 - IATA.
Text of risk phrases in Section 3	R36/38 - Irritating to eyes and skin. R43 - May cause sensitisation by skin contact. R45 - May cause cancer. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Text of Hazard Statements in Section 3	Carc. 1B: H350 - May cause cancer . Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Carc. 1B: H350i - May cause cancer by inhalation.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--