

IMPREGNATING SEALER



Impregnating Sealer is an advanced, solvent based surface protector and colour enhancer. It is ideal for providing a water repellent, stain resistant seal to slate and porous tiles, while improving and intensifying colour.



**ADVANCED IMPREGNATOR FOR POROUS TILES
PROVIDES A WATER REPELLENT SEAL
ENHANCES COLOUR OF TREATED SURFACE**

TECHNICAL INFORMATION:

PRODUCT INFORMATION	
FORM:	Liquid
COLOUR:	Clear to Pale Amber
HAZARD INFORMATION:	FLAMMABLE – Consult Safety Datasheet before use. Contains: White Spirit VOC content less than 750g/L
CLEANING:	Clean tools, equipment, etc. using white spirit or thinners.
PACKAGING:	1L Plastic Containers
STORAGE CONDITIONS:	Store in sealed containers in dry conditions, protected from extremes of temperature
SHELF LIFE:	12 months in unopened manufacturer's packaging
APPLICATION INFORMATION	
APPLICATION TEMPERATURE:	+3°C to +30°C
COVERAGE:	2-10 m ² /L depending on dilution
EXPECTED LIFE:	3 - 5 years depending on traffic, etc.

DIRECTIONS FOR USE:

NOTE

While Impregnating Sealer is suitable for almost all porous surfaces, it is recommended to always test on an inconspicuous area first to ensure suitability for use. Particular care should be taken to protect the surrounding surfaces.

SUITABILITY

Suitable for use on slate, quarry tiles, certain types of natural stone, unglazed ceramics and cement based grout.

DIRECTIONS

Supplied ready for use, do not further dilute. Surface to be treated should be clean, free from staining and contamination. Any existing stains will be almost impossible to remove following treatment. If the floor has been cleaned recently allow surface to dry for 3 days. (Underfloor heating should be switched off 24 hours prior to application.) Apply in a thin layer uniformly with a cloth, brush or sponge and allow to penetrate for approximately 15-30 minutes. Then remove all excess product from the surface with a clean lint-free cloth. Very porous surfaces may require further treatments as above. Should any product remain on the surface, remove by further buffing with a clean cloth. Surface can be walked on after 6 hours and fully trafficked after 2-3 days.