

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Larsolve Thinners

Revision 8 Revision date 2023-10-31

| SECTION 1: Identification of the substance/mixture and | of the company/undertaking |
|--|----------------------------|
|--|----------------------------|

1.1. Product identifier

| Product name |
|---------------------------------|
| Other means of identification / |
| UFI |

Larsolve Thinners

UFI: N73T-CYFE-X99F-FKWK.

1.2. Relevant identified uses of the substance or mixture and uses advised against

| Product Use | [SU22] Professional uses: Public domain (administration, education, entertainment, services, |
|-------------|--|
| | craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC10] Roller application or |
| | brushing; |

1.3. Details of the supplier of the safety data sheet

| Larsen Building Products Ltd |
|------------------------------|
| |

Address 4 West Bank Road

Belfast Harbour Industrial Estate

Belfast BT3 9JL

United Kingdom

Web www.larsenbuildingproducts.com

Telephone +44 (0)28 9077 4000 Fax +44 (0)28 9077 6945

Email I.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number

| Emergency telephone number | (00353 |
|----------------------------|--------|
|----------------------------|--------|

Company

(00353) 01 809 2166

National Poisons Centre of Ireland

8am-10pm 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

| 2.1.2. Classification - EC | Flam. Liq. 3: H226; Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332; |
|----------------------------|--|
| 1272/2008 | STOT SE 3: H336; |

2.2. Label elements

Hazard pictograms





Signal Word

Hazard Statement

Warning

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Acute Tox. 4: H312 - Harmful in contact with skin.

Skin Irrit. 2: H315 - Causes skin irritation.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Acute Tox. 4: H332 - Harmful if inhaled.

Revision 8 Revision date 2023-10-31

2.2. Label elements

| | STOT SE 3: H336 - May cause drowsiness or dizziness. | | | | | |
|--------------------------|--|--|--|--|--|--|
| Precautionary Statement: | P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No | | | | | |
| Prevention | smoking. | | | | | |
| | P233 - Keep container tightly closed. | | | | | |
| | P240 - Ground/bond container and receiving equipment. | | | | | |
| | P241 - Use explosion-proof electrical/ventilating/lighting// equipment. | | | | | |
| | P242 - Use only non-sparking tools. | | | | | |
| | P243 - Take precautionary measures against static discharge. | | | | | |
| | P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. | | | | | |
| | P264 - Wash thoroughly after handling. | | | | | |
| | P271 - Use only outdoors or in a well-ventilated area. | | | | | |
| | P280 - Wear protective gloves/protective clothing/eye protection/face protection. | | | | | |
| Precautionary Statement: | P302+P352 - IF ON SKIN: Wash with plenty of water/ . | | | | | |
| Response | P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse | | | | | |
| | skin with water/shower. | | | | | |
| | P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. | | | | | |
| | P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact | | | | | |
| | lenses, if present and easy to do. Continue rinsing. | | | | | |
| | P312 - Call a POISON CENTER/doctor/ /if you feel unwell. | | | | | |
| | P321 - Specific treatment (see on this label). | | | | | |
| | P332+P313 - If skin irritation occurs: Get medical advice/attention. | | | | | |
| | P337+P313 - If eye irritation persists: Get medical advice/attention. | | | | | |
| | P370+P378 - In case of fire: Use to extinguish. | | | | | |
| Precautionary Statement: | P403+P233 - Store in a well-ventilated place. Keep container tightly closed. | | | | | |
| Storage | P403+P235 - Store in a well-ventilated place. Keep cool. | | | | | |
| | P405 - Store locked up. | | | | | |
| Precautionary Statement: | P501 - Dispose of contents/container to appropriate waste disposal site | | | | | |
| Disposal | | | | | | |

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification |
|--|--------------|-----------|-----------|------------------------------|-----------------|--|
| Xylene (Xylene, o-,m-,-p-or mixed isomers) | 601-022-00-9 | 1330-20-7 | 215-535-7 | | 70 - 80% | Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315; |
| Isopropanol (Propan-2-ol) | 603-117-00-0 | 67-63-0 | 200-661-7 | | 20 - 30% | 7 Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; |

SECTION 4: First aid measures

4.1. Description of first aid measures

| Inhalation | Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention. |
|--------------|---|
| Eye contact | May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist. |
| Skin contact | May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist. |
| Ingestion | Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label. |

SECTION 5: Firefighting measures

5.1. Extinguishing media

Revision 8 Revision date 2023-10-31

| 5.1. Extinguishing media | | | | |
|-----------------------------------|--|--|--|--|
| | Use as appropriate: Carbon dioxide (CO2 | 2), Dry chemical, Foam. | | |
| 5.2. Special hazards arising from | n the substance or mixture | | | |
| | . Burning produces irritating, toxic and obnoxious fumes. | | | |
| 5.3. Advice for firefighters | | | | |
| | Wear suitable respiratory equipment whe | n necessary. | | |
| SECTION 6: Accidental rele | ase measures | | | |
| 6.1. Personal precautions, prote | ctive equipment and emergency procedure | S | | |
| | Ensure adequate ventilation of the workin protective equipment. | g area. Eliminate all sources of ignition. Wear suitable | | |
| 6.2. Environmental precautions | | | | |
| | Do not allow product to enter drains. Prev | vent further spillage if safe. | | |
| 6.3. Methods and material for co | ontainment and cleaning up | | | |
| | Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. | | | |
| SECTION 7: Handling and s | torage | | | |
| 7.1. Precautions for safe handlir | ng | | | |
| | Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing. | | | |
| 7.2. Conditions for safe storage, | including any incompatibilities | | | |
| | Keep in a cool, dry, well ventilated area. I | Keep containers tightly closed. | | |
| SECTION 8: Exposure contr | ols/personal protection | | | |
| 8.1. Control parameters | · · · · · · · · · · · · · · · · · · · | | | |
| · | | | | |
| 8.1.1. Exposure Limit Values | | | | |
| Isopropanol (Propan-2-ol) | WEL 8-hr limit ppm: 400 | WEL 8-hr limit mg/m3: 999 | | |
| | WEL 15 min limit ppm: 500 | WEL 15 min limit mg/m3: 1250 | | |
| | WEL 8-hr limit mg/m3 total - | WEL 15 min limit mg/m3 total - | | |
| | inhalable dust: WEL 8-hr limit mg/m3 total - | inhalable dust: WEL 15 min limit mg/m3 total - | | |
| | respirable dust: | respirable dust: | | |
| Xylene (Xylene, o-,m-,-p-or | WEL 8-hr limit ppm: 50 | WEL 8-hr limit mg/m3: 220 | | |
| mixed isomers) | WEL 15 min limit ppm: 100 | WEL 15 min limit mg/m3: 441 | | |

8.2. Exposure controls

| 8.2.1. Appropriate engineering | Ensure adequate ventilation of the working area. | | | |
|--------------------------------|--|--|--|--|
| controls | | | | |
| 8.2.2. Individual protection | Wear chemical protective clothing. | | | |
| measures | | | | |
| Eye / face protection | Approved safety goggles. | | | |
| Skin protection - | Chemical resistant gloves (PVC). | | | |
| Handprotection | | | | |

WEL 8-hr limit mg/m3 total -

WEL 8-hr limit mg/m3 total -

inhalable dust:

respirable dust:

WEL 15 min limit mg/m3 total -

WEL 15 min limit mg/m3 total -

inhalable dust:

respirable dust:

Revision 8 Revision date 2023-10-31

8.2. Exposure controls

Self-contained breathing apparatus. Wear protective clothing Respiratory protection

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid

> Colour Colourless to straw yellow

Odour Solvent

> Not relevant pН

Initial boiling point 121 - 144

> Flash point 25

Flammability (solid, gas) Flammable

Upper Explosive Limit Not determined

Lower Explosive Limit Not determined

> Vapour pressure Not determined

Relative Vapour Density Not determined

Density / Relative Density 0.9

> **Fat Solubility** Soluble

Partition coefficient Not determined

(n-octanol/water)

Autoignition temperature

Not determined Not determined

Decomposition temperature Viscosity

Not relevant

Explosive properties

Can form explosive mixtures with air

9.2. Other information

Specific gravity 0.9 g/cm³

Water solubility

Insoluble in water.

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Oxidising agents.

10.4. Conditions to avoid

Heat, sparks and open flames.

SECTION 11: Toxicological information

11.1 Information on hazard classes

| Acute toxicity Harmful by inhalation and in contact with skin. | |
|---|--|
| Skin corrosion/irritation Causes skin irritation. | |
| Serious eye damage/irritation Causes serious eye irritation. | |
| Respiratory or skin May cause drowsiness or dizziness. | |
| sensitisation | |
| Germ cell mutagenicity Not classified (Based on available data, the classification criteria are not met). | |

Carcinogenicity Not classified (Based on available data, the classification criteria are not met).

Reproductive toxicity Not classified (Based on available data, the classification criteria are not met).

STOT-single exposure May cause drowsiness or dizziness.

Revision 8 Revision date 2023-10-31

| 11 | 1.1 | Inf | orma | ation | on | hazar | d c | lasses |
|----|-----|-----|------|-------|----|-------|-----|--------|
|----|-----|-----|------|-------|----|-------|-----|--------|

STOT-repeated exposure Not classified (Based on available data, the classification criteria are not met).

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms





| 1 | 4.1 | L | Ш | N | ln | u | m | b | er |
|---|-----|---|---|---|----|---|---|---|----|
| | | | | | | | | | |

UN1307

14.2. UN proper shipping name

XYLENES

14.3. Transport hazard class(es)

| ADR/RID | 3 |
|---------|---|
| | |

Subsidiary risk

IMDG 3

Subsidiary risk - IATA 3

_

Subsidiary risk

14.4. Packing group

Packing group

14.5. Environmental hazards

Environmental hazards Yes

Marine pollutant Yes

ADR/RID

Hazard ID 33 Tunnel Category (D/E)

IMDG

EmS Code F-E S-D

IATA

Packing Instruction (Cargo) 364
Maximum quantity 60 L
Packing Instruction 353
(Passenger)

Revision 8 Revision date 2023-10-31

| | • | | _ | | |
|---|---|---|---|---|---|
| ı | Δ | · | | L | ١ |
| ı | _ | | | , | • |

| Maximum quantity | 5 L |
|------------------|-----|
|------------------|-----|

SECTION 15: Regulatory information

| SECTION 16: Other information | | | | |
|--|---|--|--|--|
| Other information | | | | |
| Revision | This document differs from the previous version in the following areas:. 2 - Hazard pictograms. | | | |
| Text of Hazard Statements in Section 3 | Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Acute Tox. 4: H332 - Harmful if inhaled. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. | | | |
| Further information | | | | |
| | The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and | | | |

combination with any other materials or in any other process.

belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in