

## SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

## Feather Edge

Revision 7 Revision date 2023-09-06

SECTION 1: Identification	of the substance/mixture and	of the company/undertaking

## 1.1. Product identifier

Product name	
Other means of identification	/
UFI	

Feather Edge

UFI: 22YH-1MJR-WA9M-N3EK.

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services,
	craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with
	intimate contact and only PPE available; [ERC3] Formulation in materials;
Description	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be

A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be mixed at the point of use with water for use in the construction industry.

## 1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
---------	------------------------------

Address 4 West Bank Road

Belfast Harbour Industrial Estate

Belfast BT3 9JL United Kingdom

Web www.larsenbuildingproducts.com

 Telephone
 +44 (0)28 9077 4000

 Fax
 +44 (0)28 9077 6945

Email I.pyper@larsenbuildingproducts.com

## 1.4. Emergency telephone number

Emergency telephone number (0

(00353) 01 809 2166

National Poisons Centre of Ireland

8am-10pm 7 days a week

## SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

2.1.2.	Classification	-	EC
1272/2	2008		

Skin Sens. 1: H317; Eye Dam. 1: H318;

#### 2.2. Label elements

Company

#### Hazard pictograms





Signal Word

Hazard Statement

Danger

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Eye Dam. 1: H318 - Causes serious eye damage.

Revision 7 Revision date 2023-09-06

_	_							
2	2		ha	م ا	Ωا	m	nte	2

Precautionary Statement: Prevention	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .
Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310 -Immediately call a POISON CENTER/doctor/ .
	P321 - Specific treatment (see on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to appropriate waste disposal site
וופטעפוע	I

#### **Further information**

This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Calcium Sulphate Hemihydrate (Plaster of Paris)		26499-65-0	231-900-3		1 - 10%	
Portland Cement		65997-15-1	266-043-4		1 - 10%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;

#### Further information

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Carbon oxides.

## 5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

#### 5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

Revision 7 Revision date 2023-09-06

6.2. Environmental precautions			
	Do not allow product to enter drains. Prevent further spillage if safe.		
6.3. Methods and material for co	ntainment and cleaning up		
	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.		
SECTION 7: Handling and si	torage		
7.1. Precautions for safe handling	ng		
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.		
7.2. Conditions for safe storage, including any incompatibilities			
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.		

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1. Exposure Limit Values

Calcium Sulphate Hemihydrate (Plaster of Paris)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
( allower of a large	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
Postland Courses	WEL 8-hr limit mg/m3 total 10 inhalable dust: WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Portland Cement	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
CONTROLS	
8.2.2. Individual protection	Appropriate dedicated workwear is generally sufficient under normal handling conditions.
measures	
Eye / face protection	Suitable eye protection.
Skin protection -	Wear suitable gloves.
Handprotection	
Skin protection - Other	After contact with skin, wash immediately with plenty of water.
Respiratory protection	Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Revision 7 Revision date 2023-09-06

#### 9.1. Information on basic physical and chemical properties

Powder Appearance Colour Grey Initial boiling point Not applicable. Flash point Not applicable. Upper Explosive Limit Not applicable. Lower Explosive Limit Not applicable. Vapour pressure Not applicable. **Relative Vapour Density** Not applicable. **Density / Relative Density** Not determined Decomposition temperature Not applicable. Viscosity Not applicable. Solubility Slightly soluble in water

#### 9.2. Other information

	_
VOC (Volatile organic	Not applicable.
compounds)	

## 9.2.2. Other safety characteristics

## SECTION 10: Stability and reactivity

	Avoid contact with: Strong acids. Avoid contact with: Strong bases.
·	

## 10.2. Chemical stability

10.1. Reactivity

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Organic materials.

#### 10.4. Conditions to avoid

Heat, sparks and open flames.

## Further information

Avoid formation of dust.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes

Acute toxicity	Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
Serious eye damage/irritation	Acute effect.
Respiratory or skin sensitisation	May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May produce an allergic reaction.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met).

#### 11.1.4. Toxicological Information

No data available

#### SECTION 12: Ecological information

Revision 7 Revision date 2023-09-06

12.1. TOXIGITY			
	No data available		
Further information			
	No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.		
SECTION 13: Disposal consi	SECTION 13: Disposal considerations		
General information			
	Dispose of in compliance with all local and national regulations. Eurpoean Waste Catalogue:. 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.		
Disposal methods			
	Do not empty into drains; dispose of this material and its container in a safe way.		
SECTION 14: Transport infor	mation		
14.1. UN number			
	The product is not classified as dangerous for carriage.		
14.2. UN proper shipping name			
	The product is not classified as dangerous for carriage.		
14.3. Transport hazard class(es)			
	The product is not classified as dangerous for carriage.		
14.4. Packing group			
	The product is not classified as dangerous for carriage.		
14.5. Environmental hazards			
	The product is not classified as dangerous for carriage.		
14.6. Special precautions for use	er en		
	The product is not classified as dangerous for carriage.		
14.7 Maritime Transport in bulk a	according to IMO instruments		
	The product is not classified as dangerous for carriage.		
Further information			
	The product is not classified as dangerous for carriage.		

## **SECTION 16: Other information**

SECTION 15: Regulatory information

Other i	intorm	ation
---------	--------	-------

Revision	This document differs from the previous version in the following areas:.  1 - Other means of identification / UFI.  1 - UFI No.	
Text of Hazard Statements in	Skin Irrit. 2: H315 - Causes skin irritation.	
Section 3	Skin Sens. 1: H317 - May cause an allergic skin reaction.	
	Eye Dam. 1: H318 - Causes serious eye damage.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use,	

Revision 7 Revision date 2023-09-06

Further information		
	relates only to the specific material designated and may not be valid for such material used in	
	combination with any other materials or in any other process.	

