

MOULD RELEASE AGENT



Larsen Mould Release Agent is a chemical release agent. It has been specifically formulated to provide easy release of formwork and to provide high quality surface finishes to concrete (including concrete produced with white cements). Mould Release Agent is suitable for use on steel, plywood, timber, G.R.P., and synthetic formwork or moulds. The use of Mould Release Agent results in greatly reduced incidence of blow holes, staining and surface blemishes.



SUITABLE ON ALL TYPES OF FORMWORK
ECONOMICAL COVERAGE RATES
DRIES IN 1-3 HOURS
EASY TO APPLY
FOR HIGH QUALITY WHITE OR GREY CONCRETE

TECHNICAL INFORMATION:

PRODUCT INFORMATION	
FORM:	Solvent based Liquid
HEALTH & SAFETY:	Flammable - Consult safety datasheet before use
CLEANING:	Clean tools with white sprit or thinners.
PACK SIZE:	5L, 25L and 200L
STORAGE:	Mould Release should be stored in closed containers protected from extremes of temperature and sources of ignition.
SHELF LIFE:	12 months in unopened manufacturer's containers.
COLOUR:	Straw
SPECIFIC GRAVITY:	0.8 g/ml
SOLUBILITY:	Insoluble in water. Soluble in white spirits (and similar organic solvents)
FLASH POINT:	38°C
COVERAGE:	Dependent on application. Approx. 25-50 m ² /L

DIRECTIONS FOR USE:**PREPARATION**

Formwork should be clean and dry.

DIRECTIONS

Mould Release Agent is supplied ready for use and should not be diluted, as this will seriously affect the properties. Apply a thin and even coat, preferably by spray. When using Mould Release Agent on unsealed timber formwork, a sealing coat should be applied, followed by a second coat prior to placing concrete. Any excess should be mopped up. Protect from rain until dry (1-3 hours depending on conditions). For best results and for highest economy, apply Mould Release Agent by spray. 9L spray units are available ex stock for this application.