

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

Easyfoam

Revision 3

Revision date 2020-09-18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Easyfoam
--------------	----------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC1] Adhesives, sealants; [PROC11] Non industrial spraying; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
-------------	--

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Resp. Sens. 1: H334; STOT SE 3: H335; Carc. 2: H351; STOT RE 2: H373;
--------------------------------------	--

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	<p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>Skin Sens. 1: H317 - May cause an allergic skin reaction.</p> <p>Eye Irrit. 2: H319 - Causes serious eye irritation.</p> <p>Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.</p> <p>STOT SE 3: H335 - May cause respiratory irritation.</p> <p>Carc. 2: H351 - Suspected of causing cancer .</p> <p>STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .</p>
Precautionary Statement: Prevention	<p>P201 - Obtain special instructions before use.</p> <p>P202 - Do not handle until all safety precautions have been read and understood.</p> <p>P260 - Do not breathe dust/fume/gas/mist/vapours/spray.</p> <p>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.</p> <p>P264 - Wash thoroughly after handling.</p>

Easyfoam

Revision 3

Revision date 2020-09-18

2.2. Label elements

Precautionary Statement: Response	P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P284 - [In case of inadequate ventilation] wear respiratory protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor/ .
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Isocyanic acid, polymethylenepolyphenylene ester		9016-87-9	618-498-9		20 - 30%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Acute Tox. 4: H332; Resp. Sens. 1: H334; STOT SE 3: H335; Carc. 2: H351; STOT RE 2: H373;
Dimethyl ether	603-019-00-8	115-10-6	204-065-8		1 - 10%	Flam. Gas 1: H220;
Isobutane	601-004-00-0	75-28-5	200-857-2		1 - 10%	Flam. Gas 1: H220;
Propane	601-003-00-5	74-98-6	200-827-9		1 - 10%	Flam. Gas 1: H220;
tris(2-chlorisopropyl)-phosphat		13674-84-5	237-158-7		1 - 10%	Acute Tox. 4: H302;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

Easyfoam

Revision 3

Revision date 2020-09-18

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Dimethyl ether	WEL 8-hr limit ppm:	400	WEL 8-hr limit mg/m3:	766
	WEL 15 min limit ppm:	500	WEL 15 min limit mg/m3:	958
	WEL 8-hr limit mg/m3 total	-	WEL 15 min limit mg/m3 total	-
	inhalable dust:		inhalable dust:	
	WEL 8-hr limit mg/m3 total	-	WEL 15 min limit mg/m3 total	-
	respirable dust:		respirable dust:	

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Easyfoam

Revision 3
Revision date 2020-09-18

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Yellow
Odour	Characteristic
Flash point	100
Upper Explosive Limit	16
Lower Explosive Limit	3

9.2. Other information

Specific gravity	1.05
VOC (Volatile organic compounds)	14.72

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Hazard pictograms

	
--	---

14.1. UN number

	UN1950
--	--------

14.2. UN proper shipping name

	AEROSOLS
--	----------

14.3. Transport hazard class(es)

ADR/RID	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63

14.4. Packing group

Packing group	-
---------------	---

Easyfoam

Revision 3

Revision date 2020-09-18

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	-
Tunnel Category	(D)

IMDG

EmS Code	F-D S-U
----------	---------

IATA

Packing Instruction (Cargo)	203
Maximum quantity	150 kg
Packing Instruction (Passenger)	203
Maximum quantity	75 kg

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 12 - 12.1. Toxicity.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H332 - Harmful if inhaled. Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. STOT SE 3: H335 - May cause respiratory irritation. Carc. 2: H351 - Suspected of causing cancer . STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Flam. Gas 1: H220 - Extremely flammable gas. Acute Tox. 4: H302 - Harmful if swallowed.
Maximum content of VOC	14.72.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--