

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

Highways RRC15

Revision Revision date 2020-08-05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	I Highways RRC15

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be
	mixed at the point of use with water for use in the construction industry.

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
---------	------------------------------

Address 4 West Bank Road

Belfast Harbour Industrial Estate

Relfast BT3 9JL

United Kingdom

Web www.larsenbuildingproducts.com

Telephone +44 (0)28 9077 4000 Fax +44 (0)28 9077 6945

Email t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC
1272/2008

Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;

2.2. Label elements

Hazard pictograms





Signal Word

Danger

Hazard Statement

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Eye Dam. 1: H318 - Causes serious eye damage.

Precautionary Statement: Prevention

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement:

P302+P352 - IF ON SKIN: Wash with plenty of water/ .

Response

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ .

P321 - Specific treatment (see on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention.

Revision 4
Revision date 2020-08-05

2.2. Label elements				
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.			
Precautionary Statement:	P501 - Dispose of contents/container to			
Disposal				
Further information				
	This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.			

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4			
Portland Cement		65997-15-1	266-043-4			Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
Calcium Sulphate		7778-18-9	231-900-3			·
Calcium Aluminate		12005-57-1	234-470-5			Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; Eye Irrit. 2: H319; STOT SE 3: H335;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

Revision 4
Revision date 2020-08-05

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Calcium Sulphate	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3:
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total
	respirable dust:	respirable dust:
Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Silica Sand (<1% Respirable	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 0.1
Quartz)	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total
	respirable dust:	respirable dust:
	i copii abie duot.	respirable dust.

8.2. Exposure controls

8.2.1. Appropriate engineering	Ensure adequate ventilation of the working area.	
controls		
8.2.2. Individual protection	Appropriate dedicated workwear is generally sufficient under normal handling conditions.	
measures		
Eye / face protection	Suitable eye protection.	
Skin protection -	Wear suitable gloves.	
Handprotection		
Skin protection - Other	After contact with skin, wash immediately with plenty of water.	
Respiratory protection	Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder/Powder	
Colour		
	Not applicable.	
Solubility	Slightly miscible in water	

SECTION 10: Stability and reactivity

10.1. Reactivity

Avoid contact with: Strong acids. Avoid contact with: Strong bases.

Revision 4
Revision date 2020-08-05

	Revision date 2020-08-05
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous re	actions
	Organic materials.
10.4. Conditions to avoid	
	Heat, sparks and open flames.
Further information	·
	Avoid formation of dust.
SECTION 11: Toxicological	information
11.1. Information on toxicological	
Acute toxicity	Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
Serious eye damage/irritation	Acute effect.
Respiratory or skin sensitisation	May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May produce an allergic reaction.
11.1.4. Toxicological Information	1
Calcium Sulphate	Oral Rat LD50: >2,000 mg/kg
SECTION 12: Foological infe	numation.
SECTION 12: Ecological info	ormation
Further information	T
	No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.
SECTION 13: Disposal cons	iderations
General information	
	Dispose of in compliance with all local and national regulations. Eurpoean Waste Catalogue:. 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.
Disposal methods	
	Do not empty into drains; dispose of this material and its container in a safe way.
SECTION 14: Transport info	rmation
14.1. UN number	
14.1. Old Hullibol	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	The product is not classified as dangerous for carriage.
14.2. Old proper shipping hame	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es	
14.3. Transport hazaru dass(es	
14.4 Packing group	The product is not classified as dangerous for carriage.
14.4. Packing group	The product is not elegated as denserous for corriers
44.5. Empiremental based	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	The ward of the offerd and decrease from the
4400 11 " 6	The product is not classified as dangerous for carriage.
14.6. Special precautions for use	
	The product is not classified as dangerous for carriage.
14.7 Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code

Revision 4
Revision date 2020-08-05

	10.000 220 20 00
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
	The product is not classified as dangerous for carriage.
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory information	

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:.
	2 - 2.1.2. Classification - EC 1272/2008.
	2 - Precautionary Statement: Prevention.
	2 - Precautionary Statement: Response.
	2 - Precautionary Statement: Storage.
Text of Hazard Statements in	Skin Irrit. 2: H315 - Causes skin irritation.
Section 3	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	Eye Dam. 1: H318 - Causes serious eye damage.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	STOT SE 3: H335 - May cause respiratory irritation.
Further information	

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.