

# SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

## Impregnating Sealer

Revision 4

Revision date 2019-12-12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	Impregnating Sealer
--------------	---------------------

#### 1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Asp. Tox. 1: H304;
--------------------------------------	--------------------

#### 2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P331 - Do NOT induce vomiting.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Impregnating Sealer

Revision 4

Revision date 2019-12-12

## 3.2. Mixtures

### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	649-405-00-X	64742-88-7	265-191-7		90 - 100%	Asp. Tox. 1: H304;
Trimethoxy (2, 4, 4 - trimethylpentyl) silane		34396-03-7			0.5 - 1%	Flam. Liq. 3: H226; Aquatic Chronic 3: H412; Aquatic Chronic 4: H413;
Methanol	603-001-00-X	67-56-1	200-659-6		0 - 0.5%	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370;

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

### 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

### 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

### 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# Impregnating Sealer

Revision 4

Revision date 2019-12-12

## 8.1. Control parameters

### 8.1.1. Exposure Limit Values

Methanol	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3: 333
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Solvent
pH	7
Initial boiling point	100

### Water solubility

	Insoluble in water.
--	---------------------

## SECTION 10: Stability and reactivity

### 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

### 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

	No data available
--	-------------------

## SECTION 13: Disposal considerations

### General information

	Dispose of in compliance with all local and national regulations.
--	---

## SECTION 14: Transport information

### Hazard pictograms

# Impregnating Sealer

Revision 4  
Revision date 2019-12-12

## Hazard pictograms



### 14.1. UN number

UN1993

### 14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S.

### 14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

### 14.4. Packing group

Packing group	III
---------------	-----

### 14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

### ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

### IMDG

EmS Code	F-E S-E
----------	---------

### IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

## SECTION 15: Regulatory information

## SECTION 16: Other information

### Other information

Text of Hazard Statements in Section 3	<p>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.</p> <p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.</p> <p>Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life.</p> <p>Flam. Liq. 2: H225 - Highly flammable liquid and vapour.</p> <p>Acute Tox. 3: H301 - Toxic if swallowed.</p> <p>Acute Tox. 3: H311 - Toxic in contact with skin.</p> <p>Acute Tox. 3: H331 - Toxic if inhaled.</p>
--	--

# Impregnating Sealer

Revision 4

Revision date 2019-12-12

---

**Other information**

	STOT SE 1: H370 - Causes damage to organs . STOT SE 2: H371 - May cause damage to organs .
--	---

---

**Further information**

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--