



Version: 01 Issued: Nov 11

EASY POST







Easy Post is a blend of specially selected aggregates, cements and additives to give a very fast-setting, cementitious, post-fixing mortar. Easy Post is ready to use directly from the bag - no mixing required. Easy Post is suitable for fixing wooden, concrete and metal posts. Fence panels can normally be fixed the same day.



SETS IN 5-10MIN
EASY TO USE
NO MIXING
SUITABLE FOR FENCEPOSTS, GATEPOSTS, GARDEN
FURNITURE AND LIGHTING



TECHNICAL DATA SHEET

Version: 01 Issued: Nov 11

TECHNICAL INFORMATION:

PRODUCT INFORMATION			
FORM:	Coarse Powder		
COLOUR:	Cement Grey		
WET DENSITY:	2300 kg/m ³		
WORKING TIME:	5 min @ 20°C		
COMPRESSIVE STRENGTH	> 20 MPa (Cured under standard lab conditions)		
USAGE:	Post 50mm (2") dia. 50mm (2") dia. 75mm x 75mm (3x3") 75mm x 75mm (3x3") 100mm x 100mm 100mm x 100mm	Hole Size 150mm x 450mm 200mm x 450mm 200mm x 600mm 300mm x 600mm 200mm x 750mm 300mm x 750mm	No. of Bags ½ bag 1 bag 1 bag 2 ½ bags ½ bags ½ bag 3 bags
NOTE:	It is important to ensure the depth of hole is sufficient based on ground conditions, height of post, usage and wind exposure		



TECHNICAL DATA SHEET

Version: 01 Issued: Nov 11

DIRECTIONS FOR USE:

- 1. Dig hole to the required depth and size for the type of post, ground conditions, and type of fencing, etc. and height of post. Usually the hole should be approximately 1/3 of the height of the finished fence. When in doubt, seek advice from the fencing supplier.
- 2. Set post centrally in hole and support vertically.
- 3. Fill hole about a third full with water (allow 3-4 L of water for each bag of Easy Post).
- 4. Carefully pour the Easy Post powder into the hole around the post until no water is visible. Sprinkle water to wet out any remaining powder on the surface. Lightly tamp the surface as required.
- 5. Quickly check and adjust position of post as necessary. Easy Post will set within 10 minutes.
- 6. Continue to support post until Easy Post has firmed up.
- 7. Fill remainder of hole with soil, and cover with turf, as required.
- 8. Fencing may be fixed on the same day.

NOTE

Easy Post will take longer to harden and set at lower temperatures, and should not be used below 5°C. Timber in contact with the ground should be suitably treated to prevent rot, i.e. pressure treated (tanalised) and care should be taken to ensure the hole is free-draining. Do not attempt to mix Easy Post with water by hand or mixer. Take care not to breathe dust - read MSDS or Health and Safety information on pack before use.

CLEANING

Clean tools, equipment, etc. using warm water. Mechanical means are necessary when the product has set.

STORAGE

Easy Post should be stored in covered, closed containers protected from extremes of temperature.

SHELF LIFE

6 months in unopened manufacturer's containers.

PACKAGING

20kg packs.