

STONE & GROUT PROTECTOR



Stone & Grout Protector is an advanced, water based surface protector based on fluoropolymers. Unlike other products, the appearance of the impregnated surface remains almost totally unchanged. Stone & Grout Protector protects treated surfaces against water and oil based staining.

ADVANCED STAIN RESISTANT IMPREGNATING SEALER
INVISIBLE PROTECTION
SUITABLE FOR ALMOST ALL POROUS SURFACES AND
ALL TYPES OF NATURAL STONE



TECHNICAL INFORMATION:

PRODUCT INFORMATION	
FORM:	Liquid
COLOUR:	Pale Amber
HAZARD INFORMATION:	IRRITANT – Consult Safety Datasheet before use. Contains: <5% Fluoropolymers
CLEANING:	Clean tools, equipment, etc. using warm water.
PACKAGING:	1L Plastic Containers
STORAGE CONDITIONS:	Store in sealed containers in dry conditions, protected from extremes of temperature
SHELF LIFE:	12 months in unopened manufacturer's packaging
APPLICATION INFORMATION	
APPLICATION TEMPERATURE:	+3°C to +30°C
COVERAGE:	5-10 m ² /L depending on dilution
EXPECTED LIFE:	5 - 10 years depending on traffic, etc.

DIRECTIONS FOR USE:

NOTE

While Stone & Grout Protector is suitable for almost all porous surfaces, it is recommended to always test on an inconspicuous area first to ensure suitability for use. Particular care should be taken to protect the surrounding surfaces.

SUITABILITY

Suitable for use on almost all porous substrates and types of natural stone.

DIRECTIONS

Supplied ready for use, do not further dilute. Surface to be treated should be clean, free from staining and contamination. Any existing stains will be almost impossible to remove following treatment. If the floor has been cleaned recently allow surface to dry for 3 days. (Underfloor heating should be switched off 24 hours prior to application.)

Apply in a thin layer uniformly with a cloth, brush or sponge and allow to penetrate for approximately 15-30 minutes. Then remove all excess product from the surface with a clean lint-free cloth. Very porous surfaces may require further treatments as above. Should any product remain on the surface, remove by further buffing with a clean cloth. Surface can be walked on after 6 hours and fully trafficked after 2-3 days.