

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

Highways MBM90

Revision 6

Revision date 2019-12-11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Highways MBM90
---------------------	----------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC5] Industrial use resulting in inclusion into or onto a matrix; [AC4] Stone, plaster, cement, glass and ceramic articles;
--------------------	---

1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	EUH203; Skin Sens. 1: H317; Eye Dam. 1: H318;
---	---

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	EUH203 - Contains chromium (VI). May produce an allergic reaction. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage.
Precautionary Statement: Prevention	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER/doctor/ . P321 - Specific treatment (see on this label).

Highways MBM90

Revision 6

Revision date 2019-12-11

2.2. Label elements

Precautionary Statement: Disposal	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4			Acute Tox. 4: H332; STOT RE 2: H373;
Calcium Sulphate Hemihydrate (Plaster of Paris)		26499-65-0	231-900-3			
Portland Cement		65997-15-1	266-043-4			Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Avoid raising dust. Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

Highways MBM90

Revision 6

Revision date 2019-12-11

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Calcium Sulphate Hemihydrate (Plaster of Paris)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Silica Sand (<1% Respirable Quartz)	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 0.1
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total respirable dust:

8.2. Exposure controls



8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection -
Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Wear: Suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Grey
Melting point	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Solubility	Miscible in water

9.2. Other information

Highways MBM90

Revision 6
Revision date 2019-12-11

9.2. Other information

Bulk Density $\approx 1.5 \text{ g/cm}^3$

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

Not determined

SECTION 12: Ecological information

12.1. Toxicity

Not determined

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

14.1. UN number

The product is not classified as dangerous for carriage.

14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

14.4. Packing group

The product is not classified as dangerous for carriage.

14.5. Environmental hazards

The product is not classified as dangerous for carriage.

14.6. Special precautions for user

The product is not classified as dangerous for carriage.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Text of Hazard Statements in Section 3

Acute Tox. 4: H332 - Harmful if inhaled.
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
 Skin Irrit. 2: H315 - Causes skin irritation.
 Skin Sens. 1: H317 - May cause an allergic skin reaction.
 Eye Dam. 1: H318 - Causes serious eye damage.

Highways MBM90

Revision 6

Revision date 2019-12-11

Other information

	STOT SE 3: H335 - May cause respiratory irritation.
--	---

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--