

VERSION: 01

ISSUED: JAN 2025

**LARSEN**

**BUILDERS MERCHANTS**

**TECHNICAL DATA SHEET**

# Black Bitumen Primer

**EASY TO APPLY**

**APPLY BY BRUSH OR AIRLESS SPRAY**

**QUICK DRYING**

Larsen Bituminous Primer is a high quality, fast drying, solvent-based bitumen primer for use with Larsen Bituminous Paint and Roofing products. Larsen Bituminous Primer should be applied prior to applying Bituminous Paint to porous substrates, such as concrete, stone, brick, etc.



**HAI** HARDWARE  
ASSOCIATION  
IRELAND  
The voice of the Irish Hardware Industry

For further information, consult our Technical Department.

Belfast 028 9077 4000 Birmingham 028 9053 5409 Dublin 01 8348255

LarsenBuildingProducts.com



## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

FORM	Black liquid
SPECIFIC GRAVITY	0.87 g/ml
FLASH POINT	44°C
HAZARD INFORMATION	Contains a flammable solvent, and all normal precautions against fire must be taken during both storage and use.
COVERAGE	Brush: 3-5 m <sup>2</sup> /L. Spray: 6-8 m <sup>2</sup> /L.

**Please note** - Not compatible with tar based substrates.

### DIRECTIONS FOR USE

#### PREPARATION

Surfaces must be dry, clean, and free from oil and any loose particles, such as rust, flaking paint, etc.

#### APPLICATION

Porous surfaces – e.g. asbestos, stone or concrete should be primed with Larsen Bituminous Primer and allowed to dry. For maximum protection of metal surfaces, it is recommended that an initial treatment of zinc phosphate primer is applied and allowed to dry. Larsen Bituminous Primer may bleed through any paints subsequently applied over it. Consult the paint manufacturer prior to application of paint for a suitable primer.

#### IMPORTANT

Keep away from sources of ignition - no smoking. Use only in well ventilated areas. Avoid contact with eyes. Wash splashes off skin. Keep out of reach of children. Consult MSDS before use.

#### CLEANING

Tools and spillages should be cleaned with white spirit.

#### STORAGE

Store in manufacturer's containers in a cool, dry, well ventilated and frost-free place.

#### SHELF LIFE

12 months in manufacturer's unopened containers.

#### PACKAGING

5L tins.