

## DECLARATION OF PERFORMANCE

in accordance with Annex III of the Construction Products Regulation (EU) No 305/2011

**No. DOP-12004-014**

1. *Unique identification code of the product-type:*

**Formulation Ref: RM011**

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Trade Name: Professional Showerproof Tile Adhesive  
Batch number: see packaging of the product**

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

**Dispersion adhesive for internal wall tiling**

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Larsen Manufacturing Ltd t/a Larsen Building Products  
4 West Bank Road  
Harbour Industrial Estate  
Belfast  
BT3 9JL**

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**not relevant**

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 3**

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

**The notified body NB1289, performed product type testing on samples and issued test report (133237)-19614.**

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

**not relevant**

9. Declared performance

Essential characteristics	Performance	Harmonised Technical specification
<b>Reaction to fire</b>	Class E <small>(as per Commission Decision 2010/81/EU)</small>	EN 12004:2007+A1:2012
<b>Release of Dangerous Substance</b>	See MSDS	
<b>Bond Strength, as:</b>		
- initial shear adhesion strength	$\geq 1.0\text{N/mm}^2$	
<b>Durability, for:</b>		
- shear adhesion strength after heat ageing	$\geq 1.0\text{N/mm}^2$	

This cementitious adhesive meets the requirements of EN12004:2007+A1:2012 for **Class D1T**.

10. *The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.*

*Signed for and on behalf of the manufacturer by:*



.....  
**Dr Rachel McGlinchey**  
**Product Development Chemist**

20/01/2022  
**Belfast**