

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Lardec

Revision 8 Revision date 2023-10-11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Draduet name

FIGURE HAITIE	
Other means of identification /	
UFI	

Lardec

UFI: WEYH-2MAC-4A9K-9FRU.

1.3. Details of the supplier of the safety data sheet

Company Larsen Building Products Ltd

Address 4 West Bank Road

Belfast Harbour Industrial Estate

Belfast BT3 9JL

United Kingdom

Web www.larsenbuildingproducts.com

 Telephone
 +44 (0)28 9077 4000

 Fax
 +44 (0)28 9077 6945

Email I.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number

Emergency telephone number

Company

(00353) 01 809 2166

National Poisons Centre of Ireland

8am-10pm 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2.	Classification - EC	
1272/	2008	

: EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;

2.2. Label elements

Hazard pictograms









Signal Word

Hazard Statement

Danger

EUH066 - Repeated exposure may cause skin dryness or cracking.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

STOT SE 3: H336 - May cause drowsiness or dizziness.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statement:

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

Revision 8 Revision date 2023-10-11

2.2. Label elements

Z.Z. Label elements				
	P240 - Ground/bond container and receiving equipment.			
	P241 - Use explosion-proof electrical/ventilating/lighting// equipment.			
	P242 - Use only non-sparking tools.			
	P243 - Take precautionary measures against static discharge.			
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.			
	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.			
	P264 - Wash thoroughly after handling.			
	P270 - Do no eat, drink or smoke when using this product.			
	P271 - Use only outdoors or in a well-ventilated area.			
	P273 - Avoid release to the environment.			
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.			
Precautionary Statement:	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ .			
Response	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse			
	skin with water/shower.			
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.			
	P314 - Get medical advice/attention if you feel unwell.			
	P331 - Do NOT induce vomiting.			
	P370+P378 - In case of fire: Use to extinguish.			
	P391 - Collect spillage.			
Precautionary Statement:	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.			
Storage	P403+P235 - Store in a well-ventilated place. Keep cool.			
	P405 - Store locked up.			
Precautionary Statement:	P501 - Dispose of contents/container to appropriate waste disposal site			
Disposal				

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Vhite Spirit					70 - 80%	: EUH066; Flam. Liq. 3:
						H226; Asp. Tox. 1: H304;
						STOT SE 3: H336; STOT RE
						1: H372; Aquatic Chronic 2:
						H411;
Resin solution in low aromatic	white				20 - 30%	EUH066; Flam. Liq. 3: H226;
spirit						STOT SE 3: H336;
Calcium 5%					0 - 0.5%	: EUH066; Eye Dam. 1:
						H318; Repr. 2: H361d;
Cobalt 10%					0 - 0.5%	Acute Tox. 4: H302; Asp.
						Tox. 1: H304; Skin Irrit. 2:
						H315; Skin Sens. 1: H317;
						Eye Irrit. 2: H319; Aquatic
						Chronic 2: H411;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Treat as for inhalation if any signs of poisoning are present. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system.

Revision 8 Revision date 2023-10-11

4.1. Description of first aid measures			
	DO NOT INDUCE VOMITING. Seek medical attention.		
SECTION 5: Firefighting measures			
5.1. Extinguishing media			
	Alcohol resistant foam. Carbon oxides.		
5.2. Special hazards arising from	n the substance or mixture		
	. Burning produces irritating, toxic and obnoxious fumes.		
5.3. Advice for firefighters			
	Wear:. Self-contained breathing apparatus. Wear chemical protective clothing.		
SECTION 6: Accidental relea	ase measures		
6.1. Personal precautions, prote	ctive equipment and emergency procedures		
	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.		
6.2. Environmental precautions			
	Do not allow product to enter drains. Prevent further spillage if safe.		
6.3. Methods and material for co	ontainment and cleaning up		
	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.		
SECTION 7: Handling and st	torage		
7.1. Precautions for safe handling	ng		
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Keep away from sources of ignition - No smoking. Use explosion proof equipment.		
7.2. Conditions for safe storage,	including any incompatibilities		
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.		
SECTION 8: Exposure contr	ols/personal protection		
8.2. Exposure controls			
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.		
8.2.2. Individual protection measures	Wear chemical protective clothing.		
Eye / face protection	Approved safety goggles.		
Skin protection - Handprotection	Chemical resistant gloves (PVC).		
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.		
SECTION 9: Physical and ch	nemical properties		

9.1. Information on basic physical and chemical properties

Revision Revision date 2023-10-11

9.1. Information on basic physical and chemical properties

Appearance Liquid Colour Various Odour Solvent

> Not relevant pН

Not determined Initial boiling point

> Flash point 38

Upper Explosive Limit Not relevant

Lower Explosive Limit Not determined

Vapour pressure

Not determined **Relative Vapour Density** Not determined

Partition coefficient

Not determined

(n-octanol/water)

Autoignition temperature

Not determined Not determined

Decomposition temperature Viscosity

Not determined

9.2. Other information

Specific gravity VOC (Volatile organic compounds)

Not determined

Not determined

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Oxidising agents.

10.4. Conditions to avoid

Heat, sparks and open flames.

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity Reproductive toxicity STOT-single exposure

May be fatal if swallowed and enters airways.

Not classified (Based on available data, the classification criteria are not met).

Not classified (Based on available data, the classification criteria are not met).

May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

Not classified (Based on available data, the classification criteria are not met).

Not classified (Based on available data, the classification criteria are not met).

Not classified (Based on available data, the classification criteria are not met).

Not classified (Based on available data, the classification criteria are not met).

Causes damage to organs through prolonged or repeated exposure .

11.1.4. Toxicological Information

STOT-repeated exposure

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

SECTION 13: Disposal considerations

Revision 8 Revision date 2023-10-11

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1300

14.2. UN proper shipping name

TURPENTINE SUBSTITUTE

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group

14.5. Environmental hazards

Environmental hazards No Marine pollutant No

ADR/RID

Hazard ID 33
Tunnel Category (D/E)

IMDG

EmS Code F-E S-E

IATA

Packing Instruction (Cargo) 364

Maximum quantity 60 L

Packing Instruction 353
(Passenger)

Maximum quantity 5 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other	infor	mation
Outer		mauon

Revision	This document differs from the previous version in the following areas:. 12 - 12.1. Toxicity.
Text of Hazard Statements in	EUH066 - Repeated exposure may cause skin dryness or cracking.
Section 3	Flam. Liq. 3: H226 - Flammable liquid and vapour.

Revision 8 Revision date 2023-10-11

Other information	
	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage. Repr. 2: H361d - Suspected of damaging the unborn child. Acute Tox. 4: H302 - Harmful if swallowed. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.