

# SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Lardec

Revision 8

Revision date 2023-10-11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

<b>Product name</b>	Lardec
<b>Other means of identification / UFI</b>	UFI: WEYH-2MAC-4A9K-9FRU.

### 1.3. Details of the supplier of the safety data sheet

<b>Company</b>	Larsen Building Products Ltd
<b>Address</b>	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
<b>Web</b>	www.larsenbuildingproducts.com
<b>Telephone</b>	+44 (0)28 9077 4000
<b>Fax</b>	+44 (0)28 9077 6945
<b>Email</b>	l.pyper@larsenbuildingproducts.com

### 1.4. Emergency telephone number


<b>Emergency telephone number</b>	(00353) 01 809 2166
<b>Company</b>	National Poisons Centre of Ireland 8am-10pm 7 days a week

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

<b>2.1.2. Classification - EC 1272/2008</b>	: EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;
---	---

### 2.2. Label elements

<b>Hazard pictograms</b>	
<b>Signal Word</b>	Danger
<b>Hazard Statement</b>	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
<b>Precautionary Statement: Prevention</b>	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed.

## Lardec

Revision 8

Revision date 2023-10-11

## 2.2. Label elements

<b>Precautionary Statement: Response</b>	P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P331 - Do NOT induce vomiting. P370+P378 - In case of fire: Use to extinguish. P391 - Collect spillage.
<b>Precautionary Statement: Storage</b>	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
<b>Precautionary Statement: Disposal</b>	P501 - Dispose of contents/container to appropriate waste disposal site

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
White Spirit					70 - 80%	: EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;
Resin solution in low aromatic white spirit					20 - 30%	EUH066; Flam. Liq. 3: H226; STOT SE 3: H336;
Calcium 5%					0 - 0.5%	: EUH066; Eye Dam. 1: H318; Repr. 2: H361d;
Cobalt 10%					0 - 0.5%	Acute Tox. 4: H302; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

<b>Inhalation</b>	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
<b>Eye contact</b>	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
<b>Skin contact</b>	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Treat as for inhalation if any signs of poisoning are present. Seek medical attention if irritation or symptoms persist.
<b>Ingestion</b>	Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system.

## Lardec

Revision 8  
Revision date 2023-10-11

## 4.1. Description of first aid measures

DO NOT INDUCE VOMITING. Seek medical attention.

**SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Alcohol resistant foam. Carbon oxides.

## 5.2. Special hazards arising from the substance or mixture

. Burning produces irritating, toxic and obnoxious fumes.

## 5.3. Advice for firefighters

Wear:. Self-contained breathing apparatus. Wear chemical protective clothing.

**SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.

## 6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

## 6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

**SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Keep away from sources of ignition - No smoking. Use explosion proof equipment.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

**SECTION 8: Exposure controls/personal protection**

## 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

## 8.2.2. Individual protection measures

Wear chemical protective clothing.

## Eye / face protection

Approved safety goggles.

Skin protection -  
Handprotection

Chemical resistant gloves (PVC).

## Respiratory protection

Self-contained breathing apparatus. Wear protective clothing.

**SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

## Lardec

Revision 8  
Revision date 2023-10-11

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Various
Odour	Solvent
pH	Not relevant
Initial boiling point	Not determined
Flash point	38
Upper Explosive Limit	Not relevant
Lower Explosive Limit	Not determined
Vapour pressure	Not determined
Relative Vapour Density	Not determined
Partition coefficient (n-octanol/water)	Not determined
Autoignition temperature	Not determined
Decomposition temperature	Not determined
Viscosity	Not determined

## 9.2. Other information

Specific gravity	Not determined
VOC (Volatile organic compounds)	Not determined

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

## 10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

## SECTION 11: Toxicological information

## 11.1 Information on hazard classes

Acute toxicity	May be fatal if swallowed and enters airways.
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met).
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met).
Respiratory or skin sensitisation	May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure .

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
--	-------------------

## SECTION 13: Disposal considerations

## Lardec


Revision 8  
Revision date 2023-10-11

## General information

	Dispose of in compliance with all local and national regulations.
--	---

## SECTION 14: Transport information

## Hazard pictograms

	
--	---

## 14.1. UN number

	UN1300
--	--------

## 14.2. UN proper shipping name

	TURPENTINE SUBSTITUTE
--	-----------------------

## 14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

## 14.4. Packing group

Packing group	II
---------------	----

## 14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

## ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

## IMDG

EmS Code	F-E S-E
----------	---------

## IATA

Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L

## SECTION 15: Regulatory information

## SECTION 16: Other information

## Other information

Revision	This document differs from the previous version in the following areas: 12 - 12.1. Toxicity.
Text of Hazard Statements in Section 3	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour.

## Lardec

Revision 8

Revision date 2023-10-11

**Other information**

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
STOT SE 3: H336 - May cause drowsiness or dizziness.  
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Eye Dam. 1: H318 - Causes serious eye damage.  
Repr. 2: H361d - Suspected of damaging the unborn child.  
Acute Tox. 4: H302 - Harmful if swallowed.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
Eye Irrit. 2: H319 - Causes serious eye irritation.

**Further information**

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.