

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Black Bitumen Paint

Revision 11

Revision date 2023-03-15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Black Bitumen Paint
Other means of identification / UFI	UFI: JFFQ-1QRA-JMK4-9S47.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
-------------	--

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	l.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number

Emergency telephone number	(00353) 01 809 2166
Company	National Poisons Centre of Ireland 8am-10pm 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	: EUH066; Flam. Liq. 3: H226; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;
--------------------------------------	--

2.2. Label elements

Hazard pictograms	
Signal Word	Danger

Hazard Statement

EUH066 - Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
STOT SE 3: H336 - May cause drowsiness or dizziness.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

Black Bitumen Paint

Revision

11

Revision date 2023-03-15

2.2. Label elements

Precautionary Statement: Prevention	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233 - Keep container tightly closed.
	P240 - Ground/bond container and receiving equipment.
Precautionary Statement: Response	P241 - Use explosion-proof electrical/ventilating/lighting// equipment.
	P242 - Use only non-sparking tools.
	P243 - Take precautionary measures against static discharge.
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
Precautionary Statement: Storage	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264 - Wash thoroughly after handling.
	P270 - Do no eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area.
Precautionary Statement: Disposal	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Precautionary Statement: Storage	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.
	P314 - Get medical advice/attention if you feel unwell.
	P370+P378 - In case of fire: Use to extinguish.
	P391 - Collect spillage.
Precautionary Statement: Disposal	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
	P403+P235 - Store in a well-ventilated place. Keep cool.
	P405 - Store locked up.
	P501 - Dispose of contents/container to licensed waste disposal site

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Oxidised Bitumen		64742-93-4	265-196-4			
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			919-446-0			: EUH066; Flam. Liq. 3; H226; Asp. Tox. 1: H304; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Black Bitumen Paint

Revision

11

Revision date

2023-03-15

5.1. Extinguishing media

Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Oxidised Bitumen	WEL 8-hr limit ppm: WEL 15 min limit ppm: WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 2.9 WEL 15 min limit mg/m3: WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
------------------	---	---

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Self-contained breathing apparatus. Wear protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Black Bitumen Paint

Revision

11

Revision date 2023-03-15

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Black
Odour	Characteristic
Initial boiling point	≥ 153 °C
Flash point	≥ 40 °C
Autoignition temperature	≥ 200 °C
Viscosity	290 x 10-6 m ² /s @ 40 °C (ISO 3104/3105)
Solubility	Insoluble in water

9.2. Other information

Specific gravity	0.89 - 0.92 g/cm ³
VOC (Volatile organic compounds)	389 g/l

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity	Not classified (Based on available data, the classification criteria are not met).
Skin corrosion/irritation	EUH066 - Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met).
Respiratory or skin sensitisation	Not classified (Based on available data, the classification criteria are not met).
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	H336 - May cause drowsiness or dizziness.
STOT-repeated exposure	H372 - Causes damage to organs through prolonged or repeated exposure .
Aspiration hazard	Aspiration hazard H304 has been eliminated due the kinematic viscosity of the product being above 20.5 mm ² /s @ 40°C.
Repeated or prolonged exposure	Repeated or prolonged exposure may cause damage to liver, kidneys and central nervous system. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

Black Bitumen Paint

Revision 11

Revision date 2023-03-15

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1999

14.2. UN proper shipping name

TARS, LIQUID

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 1 - Other means of identification / UFI. 11 - Acute toxicity. 11 - Skin corrosion/irritation. 11 - Respiratory or skin sensitisation. 11 - Repeated or prolonged exposure. 11 - Germ cell mutagenicity.
----------	---

Black Bitumen Paint

Revision

11

Revision date 2023-03-15

Other information

	11 - Carcinogenicity. 11 - Reproductive toxicity. 11 - Serious eye damage/irritation. 11 - STOT-single exposure. 11 - STOT-repeated exposure. 11 - Aspiration hazard.
Text of Hazard Statements in Section 3	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Maximum content of VOC	389 g/l.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--