

# SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/4

## Epoxy Tile Grout Pt A

Revision 5  
Revision date 2020-08-10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

<b>Product name</b>	Epoxy Tile Grout Pt A
---------------------	-----------------------

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Product Use</b>	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC3] Formulation in materials;
--------------------	--

#### 1.3. Details of the supplier of the safety data sheet


<b>Company</b>	Larsen Building Products Ltd
<b>Address</b>	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
<b>Web</b>	www.larsenbuildingproducts.com
<b>Telephone</b>	+44 (0)28 9077 4000
<b>Fax</b>	+44 (0)28 9077 6945
<b>Email</b>	t.moore@larsenbuildingproducts.com

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

<b>2.1.2. Classification - EC 1272/2008</b>	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;
---	---

#### 2.2. Label elements

<b>Hazard pictograms</b>	
<b>Signal Word</b>	Warning
<b>Hazard Statement</b>	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
<b>Precautionary Statement: Prevention</b>	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
<b>Precautionary Statement: Response</b>	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## Epoxy Tile Grout Pt A

Revision 5

Revision date 2020-08-10

## 2.2. Label elements

Precautionary Statement: Disposal	P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P391 - Collect spillage.
	P501 - Dispose of contents/container to

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5			Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411;
Bisphenol F Type Epoxy Resin		28064-14-4				Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;
Oxiran, Mono[(C12-14-alkyloxy)methyl]- derivative	603-103-00-4	68609-97-2	271-846-8			Skin Irrit. 2: H315; Skin Sens. 1: H317;

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Carbon oxides.
--	----------------

## 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

## 5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

## 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

## 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

## Epoxy Tile Grout Pt A

Revision 5  
Revision date 2020-08-10

## 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

## 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

## SECTION 8: Exposure controls/personal protection

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless to straw yellow
Odour	Characteristic

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

## General information

	Dispose of in compliance with all local and national regulations.
--	---

## SECTION 14: Transport information

## Hazard pictograms

	
--	---

## 14.1. UN number

	UN3077
--	--------

## Epoxy Tile Grout Pt A

Revision 5

Revision date 2020-08-10

## 14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

## 14.3. Transport hazard class(es)

ADR/RID	9
Subsidiary risk	-
IMDG	9
Subsidiary risk	-
IATA	9
Subsidiary risk	-

## 14.4. Packing group

Packing group III

## 14.5. Environmental hazards

Environmental hazards	Yes
Marine pollutant	Yes

## ADR/RID

Hazard ID	90
Tunnel Category	(E)

## IMDG

EmS Code F-A S-F

## IATA

Packing Instruction (Cargo)	956
Maximum quantity	400 kg
Packing Instruction (Passenger)	956
Maximum quantity	400 kg

## Further information

The product is not classified as dangerous for carriage.

## SECTION 15: Regulatory information

## SECTION 16: Other information

## Other information

Revision	This document differs from the previous version in the following areas: 8 - Respiratory protection.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

## Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

# SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/4

## Epoxy Tile Grout Pt B

Revision 4

Revision date 2020-08-10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

<b>Product name</b>	Epoxy Tile Grout Pt B
---------------------	-----------------------

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Product Use</b>	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC3] Formulation in materials;
--------------------	--

#### 1.3. Details of the supplier of the safety data sheet


<b>Company</b>	Larsen Building Products Ltd
<b>Address</b>	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
<b>Web</b>	www.larsenbuildingproducts.com
<b>Telephone</b>	+44 (0)28 9077 4000
<b>Fax</b>	+44 (0)28 9077 6945
<b>Email</b>	t.moore@larsenbuildingproducts.com

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

<b>2.1.2. Classification - EC 1272/2008</b>	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 3: H412;
---	---

#### 2.2. Label elements

<b>Hazard pictograms</b>	
<b>Signal Word</b>	Warning
<b>Hazard Statement</b>	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
<b>Precautionary Statement: Prevention</b>	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
<b>Precautionary Statement: Response</b>	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## Epoxy Tile Grout Pt B

Revision 4  
Revision date 2020-08-10

## 2.2. Label elements

Precautionary Statement: Disposal	P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.
	P501 - Dispose of contents/container to

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Polyamine Hardener		155240-10-1				Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 3: H412;

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Carbon oxides.
--	----------------

## 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

## 5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

## 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

## 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

## 7.2. Conditions for safe storage, including any incompatibilities

## Epoxy Tile Grout Pt B

Revision 4

Revision date 2020-08-10

## 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

## SECTION 8: Exposure controls/personal protection

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless to straw yellow
Odour	Characteristic

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
--	-------------------

## SECTION 13: Disposal considerations

## General information

	Dispose of in compliance with all local and national regulations.
--	---

## SECTION 14: Transport information

## 14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

## 14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

## 14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

## 14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

## 14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

## Epoxy Tile Grout Pt B

Revision 4

Revision date 2020-08-10

**14.6. Special precautions for user**

	The product is not classified as dangerous for carriage.
--	--

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

	The product is not classified as dangerous for carriage.
--	--

**Further information**

	The product is not classified as dangerous for carriage.
--	--

**SECTION 15: Regulatory information****SECTION 16: Other information****Other information****Revision**

	This document differs from the previous version in the following areas: 8 - Respiratory protection.
--	--

**Text of Hazard Statements in Section 3**

	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
--	---

**Further information**

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--



# SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

## Epoxy Tile Grout Pt C

Revision 8

Revision date 2020-08-10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

<b>Product name</b>	Epoxy Tile Grout Pt C
---------------------	-----------------------

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Product Use</b>	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC3] Formulation in materials; [AC4] Stone, plaster, cement, glass and ceramic articles;
<b>Description</b>	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be mixed at the point of use with water for use in the construction industry.

#### 1.3. Details of the supplier of the safety data sheet


<b>Company</b>	Larsen Building Products Ltd
<b>Address</b>	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
<b>Web</b>	www.larsenbuildingproducts.com
<b>Telephone</b>	+44 (0)28 9077 4000
<b>Fax</b>	+44 (0)28 9077 6945
<b>Email</b>	t.moore@larsenbuildingproducts.com

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

<b>2.1.2. Classification - EC 1272/2008</b>	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
---	--

#### 2.2. Label elements

<b>Hazard pictograms</b>	
<b>Signal Word</b>	Danger
<b>Hazard Statement</b>	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage.
<b>Precautionary Statement: Prevention</b>	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
<b>Precautionary Statement: Response</b>	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

## Epoxy Tile Grout Pt C

Revision 8

Revision date 2020-08-10

## 2.2. Label elements

Precautionary Statement: Disposal	lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER/doctor/ . P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P501 - Dispose of contents/container to

## Further information

	This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.
--	---

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Portland Cement		65997-15-1	266-043-4			Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
Barium Sulphate		7727-43-7				
Silica Flour		14808-60-7				

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Carbon oxides.
--	----------------

## 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

## 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

## 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

## 6.3. Methods and material for containment and cleaning up

	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly
--	--

## Epoxy Tile Grout Pt C

Revision 8

Revision date 2020-08-10

## 6.3. Methods and material for containment and cleaning up

with plenty of water.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1. Exposure Limit Values

Barium Sulphate	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Appropriate dedicated workwear is generally sufficient under normal handling conditions.
Eye / face protection	Suitable eye protection.
Skin protection - Handprotection	Wear suitable gloves.
Skin protection - Other	After contact with skin, wash immediately with plenty of water.
Respiratory protection	Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Various
Odour	Faint

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

Avoid contact with: Strong acids. Avoid contact with: Strong bases.

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

## Epoxy Tile Grout Pt C

Revision 8

Revision date 2020-08-10

## 10.3. Possibility of hazardous reactions

Organic materials.

## 10.4. Conditions to avoid

Heat, sparks and open flames.

## Further information

Avoid formation of dust.

**SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity	Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
Serious eye damage/irritation	Acute effect.
Respiratory or skin sensitisation	May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May produce an allergic reaction.

## 11.1.4. Toxicological Information

No data available

**SECTION 12: Ecological information**

## 12.1. Toxicity

No data available

## Further information

No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.

**SECTION 13: Disposal considerations**

## General information

Dispose of in compliance with all local and national regulations. Eurpoean Waste Catalogue:. 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.

## Disposal methods

Do not empty into drains; dispose of this material and its container in a safe way.

**SECTION 14: Transport information**

## 14.1. UN number

The product is not classified as dangerous for carriage.

## 14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

## 14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

## 14.4. Packing group

The product is not classified as dangerous for carriage.

## 14.5. Environmental hazards

The product is not classified as dangerous for carriage.

## 14.6. Special precautions for user

The product is not classified as dangerous for carriage.

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

## Epoxy Tile Grout Pt C

Revision 8

Revision date 2020-08-10

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

## Further information

	The product is not classified as dangerous for carriage.
--	--

## SECTION 15: Regulatory information

## SECTION 16: Other information

## Other information

Revision	This document differs from the previous version in the following areas: 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage.

## Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--