

# SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

## Lartex Epoxy Bond Pt A

Revision 7

Revision date 2020-09-25

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	Lartex Epoxy Bond Pt A
--------------	------------------------

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact); [ERC3] Formulation in materials;
-------------	---

#### 1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;
--------------------------------------	---

#### 2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

# Lartex Epoxy Bond Pt A

Revision 7

Revision date 2020-09-25

## 2.2. Label elements

Precautionary Statement: Disposal	lenses, if present and easy to do. Continue rinsing. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P391 - Collect spillage.
	P501 - Dispose of contents/container to

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5			Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411;
Barium Sulphate		7727-43-7				
Silica Flour		14808-60-7				
Oxiran, Mono[(C12-14-alkyloxy)methyl]- derivative Bisphenol F Type Epoxy Resin	603-103-00-4	68609-97-2	271-846-8			Skin Irrit. 2: H315; Skin Sens. 1: H317; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;
Titanium Dioxide		13463-67-7	236-675-5			
Talc (Talc, respirable dust)		14807-96-6				

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Carbon oxides.
--	----------------

### 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

### 5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

### 6.2. Environmental precautions

# Lartex Epoxy Bond Pt A

Revision 7

Revision date 2020-09-25

## 6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

## 6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Exposure Limit Values

Barium Sulphate	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Talc (Talc, respirable dust)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 1
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Titanium Dioxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

### 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

## Lartex Epoxy Bond Pt A

Revision 7  
Revision date 2020-09-25

## 9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	Grey
Odour	Characteristic
Solubility	Insoluble in water

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

## General information

	Dispose of in compliance with all local and national regulations.
--	---

## SECTION 14: Transport information

## Hazard pictograms

	 
--	---

## 14.1. UN number

	UN3082
--	--------

## 14.2. UN proper shipping name

	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
--	---

## 14.3. Transport hazard class(es)

ADR/RID	9
Subsidiary risk	-
IMDG	9
Subsidiary risk	-
IATA	9
Subsidiary risk	-

## 14.4. Packing group

Packing group	III
---------------	-----

## 14.5. Environmental hazards

Environmental hazards	Yes
Marine pollutant	Yes

ADR/RID	
Hazard ID	90

## Lartex Epoxy Bond Pt A

Revision 7  
Revision date 2020-09-25

## ADR/RID

Tunnel Category	(E)
-----------------	-----

## IMDG

EmS Code	F-A S-F
----------	---------

## IATA

Packing Instruction (Cargo)	964
Maximum quantity	450 L
Packing Instruction (Passenger)	964
Maximum quantity	450 L

## Further information

	The product is not classified as dangerous for carriage.
--	--

## SECTION 15: Regulatory information

## SECTION 16: Other information

## Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <p>2 - 2.1.2. Classification - EC 1272/2008.</p> <p>2 - Hazard pictograms.</p> <p>2 - Signal Word.</p> <p>2 - Precautionary Statement: Prevention.</p> <p>2 - Precautionary Statement: Response.</p> <p>2 - Precautionary Statement: Storage.</p>
Text of Hazard Statements in Section 3	<p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>Skin Sens. 1: H317 - May cause an allergic skin reaction.</p> <p>Eye Irrit. 2: H319 - Causes serious eye irritation.</p> <p>Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.</p>

## Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---

# SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/4

## Lartex Epoxy Bond Pt B

Revision 7

Revision date 2019-12-17

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	Lartex Epoxy Bond Pt B
--------------	------------------------

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact); [ERC3] Formulation in materials;
-------------	---

#### 1.3. Details of the supplier of the safety data sheet


Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	t.moore@larsenbuildingproducts.com

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Acute Tox. 4: H302; Acute Tox. 4: H312; Skin Corr. 1B: H314; Skin Sens. 1: H317; STOT SE 3: H335; Aquatic Chronic 3: H412;
--------------------------------------	--

#### 2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace.



# Lartex Epoxy Bond Pt B

Revision 7

Revision date 2019-12-17

## 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	---

## 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

## 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

## SECTION 8: Exposure controls/personal protection

### 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Amber
Odour	Characteristic
Initial boiling point	204 °C
Flash point	195 °C
Vapour pressure	20.68
Relative density	0.95

## SECTION 10: Stability and reactivity

### 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Skin corrosion/irritation	Causes burns.
---------------------------	---------------

### 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

	No data available
--	-------------------



# Lartex Epoxy Bond Pt B

Revision 7

Revision date 2019-12-17

## SECTION 13: Disposal considerations

### General information

Dispose of in compliance with all local and national regulations.

## SECTION 14: Transport information

### 14.1. UN number

The product is not classified as dangerous for carriage.

### 14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

### 14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

### 14.4. Packing group

The product is not classified as dangerous for carriage.

### 14.5. Environmental hazards

The product is not classified as dangerous for carriage.

### 14.6. Special precautions for user

The product is not classified as dangerous for carriage.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

## SECTION 15: Regulatory information

## SECTION 16: Other information

### Other information

#### Text of Hazard Statements in Section 3

Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin  
 Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.  
 Skin Sens. 1: H317 - May cause an allergic skin reaction.  
 STOT SE 3: H335 - May cause respiratory irritation.  
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

### Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.