

# SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

## Acrylic Concrete Sealer

Revision 6

Revision date 2023-06-28

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

<b>Product name</b>	Acrylic Concrete Sealer
<b>Other means of identification / UFI</b>	UFI: Y3SQ-DRFE-Y999-498R.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Product Use</b>	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC10] Roller application or brushing; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
--------------------	---

#### 1.3. Details of the supplier of the safety data sheet

<b>Company</b>	Larsen Building Products Ltd
<b>Address</b>	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
<b>Web</b>	www.larsenbuildingproducts.com
<b>Telephone</b>	+44 (0)28 9077 4000
<b>Fax</b>	+44 (0)28 9077 6945
<b>Email</b>	l.pyper@larsenbuildingproducts.com

#### 1.4. Emergency telephone number


<b>Emergency telephone number</b>	(00353) 01 809 2166
<b>Company</b>	National Poisons Centre of Ireland 8am-10pm 7 days a week

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

<b>2.1.2. Classification - EC 1272/2008</b>	Flam. Liq. 3: H226; Acute Tox. 4: H312; Skin Irrit. 2: H315; Acute Tox. 4: H332;
---	--

#### 2.2. Label elements

<b>Hazard pictograms</b>	
<b>Signal Word</b>	Warning
<b>Hazard Statement</b>	Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Acute Tox. 4: H332 - Harmful if inhaled.

# Acrylic Concrete Sealer

Revision 6

Revision date 2023-06-28

## 2.2. Label elements

<b>Precautionary Statement: Prevention</b>	<p>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 - Keep container tightly closed.</p> <p>P240 - Ground/bond container and receiving equipment.</p> <p>P241 - Use explosion-proof electrical/ventilating/lighting// equipment.</p> <p>P242 - Use only non-sparking tools.</p> <p>P243 - Take precautionary measures against static discharge.</p> <p>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.</p> <p>P264 - Wash thoroughly after handling.</p> <p>P271 - Use only outdoors or in a well-ventilated area.</p> <p>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</p>
<b>Precautionary Statement: Response</b>	<p>P302+P352 - IF ON SKIN: Wash with plenty of water/ .</p> <p>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 - Call a POISON CENTER/doctor/ /if you feel unwell.</p> <p>P321 - Specific treatment (see on this label).</p> <p>P332+P313 - If skin irritation occurs: Get medical advice/attention.</p> <p>P370+P378 - In case of fire: Use to extinguish.</p>
<b>Precautionary Statement: Storage</b>	P403+P235 - Store in a well-ventilated place. Keep cool.
<b>Precautionary Statement: Disposal</b>	P501 - Dispose of contents/container to appropriate waste container

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7		80 - 90%	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Inhalation</b>	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
<b>Eye contact</b>	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
<b>Skin contact</b>	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
<b>Ingestion</b>	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

### 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

### 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

# Acrylic Concrete Sealer

Revision 6

Revision date 2023-06-28

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

### 6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

### 6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Exposure Limit Values

Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

### 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

## Acrylic Concrete Sealer

Revision 6

Revision date 2023-06-28

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Solvent
pH	Not applicable.
Melting point	-95 - 13 °C
Freezing Point	Not determined
Initial boiling point	136 - 152 °C
Flash point	≥ 23 °C
Upper Explosive Limit	1 %
Lower Explosive Limit	7 %
Vapour pressure	≥ 650 Pa
Relative Vapour Density	Not determined
Partition coefficient (n-octanol/water)	Not determined
Autoignition temperature	> 432 °C
Decomposition temperature	Not determined
Viscosity	Not applicable.
Explosive properties	Not determined
Solubility	Immiscible in water

## 9.2. Other information

Specific gravity	0.89 - 0.93 g/cm <sup>3</sup>
VOC (Volatile organic compounds)	Not determined

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

## 11.1 Information on hazard classes

Acute toxicity	Harmful by inhalation and in contact with skin.
Skin corrosion/irritation	CAUSES SKIN IRRITATION.
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met).
Respiratory or skin sensitisation	Causes skin irritation. Harmful by inhalation and in contact with skin.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met).
Aspiration hazard	Not classified (Based on available data, the classification criteria are not met).
Repeated or prolonged exposure	Not classified (Based on available data, the classification criteria are not met).

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
--	-------------------

## Acrylic Concrete Sealer

Revision 6

Revision date 2023-06-28

**SECTION 13: Disposal considerations**

## General information

Dispose of in compliance with all local and national regulations.

**SECTION 14: Transport information**

## Hazard pictograms



## 14.1. UN number

UN1307

## 14.2. UN proper shipping name

XYLENES

## 14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

## 14.4. Packing group

Packing group III

## 14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

## ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

## IMDG

EmS Code F-E S-D

## IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

**SECTION 15: Regulatory information****SECTION 16: Other information**

## Other information

Revision This document differs from the previous version in the following areas:  
2 - 2.1. Classification of the substance or mixture.

# Acrylic Concrete Sealer

Revision 6

Revision date 2023-06-28

## Other information

Text of Hazard Statements in Section 3	2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 15 - Risk phrases.
	Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Acute Tox. 4: H332 - Harmful if inhaled.

## Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--