


LARSEN
BUILDERS MERCHANTS
TECHNICAL DATA SHEET

Roofing Compound (Trowel Grade)

EASY TO APPLY
READY TO USE
WATER-RESISTANT
**UNAFFECTED BY RAIN OR
FROST IMMEDIATELY AFTER
APPLICATION**

Roofing Compound (Trowel Grade) is a solvent-based, thick, heavy-bodied, bituminous compound with excellent non-slump characteristics. It is principally used for repairing cracks in all types of roofs, including asphalt, bitumen felt, asbestos, cement, concrete, etc. Roofing Compound (Trowel Grade) is ideal for use as a glazing bar mastic on roof lights.



HAI **HARDWARE
ASSOCIATION
IRELAND**
The voice of the Irish Hardware Industry

TECHNICAL DATA SHEET

PRODUCT INFORMATION

FORM	Black Paste
MATERIAL	Bituminous Mastic
PACKAGING	2.5kg and 5kg metal paint tins
CLEANING	Tools and spillages should be cleaned with white spirit.
STORAGE CONDITIONS	Store in manufacturer's containers in a cool, dry, well ventilated and frost-free place out of direct sunlight.
SHELF LIFE	12 months in manufacturer's unopened containers.
FLASH POINT	39°C
WATER RESISTANCE	Resistant to water when dried
COVERAGE	0.7 m ² /kg @ 1 mm

DIRECTIONS FOR USE

PREPARATION

Surfaces should be clean, and free from grease, dust and loose debris. Lichen and moss should be removed and the surface treated with Larsen Concentrated Algicide. Roofing Compound Trowel Grade can be applied to damp not wet surfaces.

PRIMING

Porous and dusty surfaces should be primed with Larsen Bitumen Primer, e.g. concrete, slate, steel, asphalt and corrugated iron.

APPLICATION

Do not thin. Non-toxic, but adequate ventilation should be provided in confined areas. Apply with a steel trowel or putty knife, which may be lubricated with Turpentine substitute or White Spirit.

RESTRICTIONS

Keep away from sources of ignition - no smoking. Use only in well ventilated areas. Avoid contact with eyes. Wash splashes off skin. Keep out of reach of children. Consult MSDS before use. Do not apply over tar based surfaces or surfaces that can rise above 65°C.