

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Larseal Impregnation Part A

Revision 7
Revision date 2023-10-25

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Larseal Impregnation Part A
Other means of identification / UFI	UFI: WD0T-PF6A-U994-MAPF.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact); [ERC3] Formulation in materials;
--------------------	---

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	l.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number


Emergency telephone number	(00353) 01 809 2166
Company	National Poisons Centre of Ireland 8am-10pm 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Acute Tox. 4: H312; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Acute Tox. 4: H332;
---	--

2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Hazard Statement	Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation.

Larseal Impregnation Part A

Revision 7

Revision date 2023-10-25

2.2. Label elements

Precautionary Statement: Prevention	Acute Tox. 4: H332 - Harmful if inhaled. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER/doctor/ if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to appropriate waste disposal site

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Epoxy Resin Solution					40 - 50%	Flam. Liq. 3: H226; Acute Tox. 4: H312+H332; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319;
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7		30 - 40%	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;
1-Methoxy-2-propanol (1-Methoxypropan-2-ol) Air Release Additive	603-064-00-3	107-98-2	203-539-1		10 - 20% 0 - 0.5%	Flam. Liq. 3: H226; STOT SE 3: H336; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

Larseal Impregnation Part A

Revision 7
Revision date 2023-10-25

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

1-Methoxy-2-propanol (1-Methoxypropan-2-ol)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 375
	WEL 15 min limit ppm: 150	WEL 15 min limit mg/m3: 560
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Larseal Impregnation Part A

Revision 7

Revision date 2023-10-25

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless to straw yellow
Odour	Characteristic
pH	Not applicable.
Initial boiling point	Not determined
Flash point	Not determined
Upper Explosive Limit	Not determined
Lower Explosive Limit	Not determined
Vapour pressure	Not determined
Relative Vapour Density	Not determined
Partition coefficient (n-octanol/water)	Not determined
Autoignition temperature	Not determined
Decomposition temperature	Not determined
Viscosity	Not applicable.
Solubility	Insoluble in water

9.2. Other information

Specific gravity	0.94 - 1.04 g/cm ³
VOC (Volatile organic compounds)	Not determined

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity	Harmful by inhalation and if swallowed.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met).

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Larseal Impregnation Part A

Revision 7
Revision date 2023-10-25

Hazard pictograms

	
--	---

14.1. UN number

	UN1307
--	--------

14.2. UN proper shipping name

	XYLENES
--	---------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-D
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 1 - Other means of identification / UFI. 9 - 9.1. Information on basic physical and chemical properties (PH). 9 - 9.1. Information on basic physical and chemical properties (Initial boiling point). 9 - 9.1. Information on basic physical and chemical properties (Flash point). 9 - 9.1. Information on basic physical and chemical properties (Autoignition temperature).
----------	--

Larseal Impregnation Part A

Revision 7

Revision date 2023-10-25

Other information

	<p>9 - 9.1. Information on basic physical and chemical properties (Vapour pressure).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Viscosity).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Relative Vapour Density).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Upper Explosive Limit).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Lower Explosive Limit).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Decomposition temperature).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Solubility).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Partition coefficient (n-octanol/water)).</p> <p>9 - 9.2. Other information (Product Subcategory).</p> <p>9 - 9.2. Other information (Specific gravity).</p> <p>11 - Acute toxicity.</p> <p>11 - Skin corrosion/irritation.</p> <p>11 - Respiratory or skin sensitisation.</p> <p>11 - Germ cell mutagenicity.</p> <p>11 - Carcinogenicity.</p> <p>11 - Reproductive toxicity.</p> <p>11 - Serious eye damage/irritation.</p> <p>11 - STOT-single exposure.</p> <p>11 - STOT-repeated exposure.</p> <p>16 - Maximum content of VOC.</p>
Text of Hazard Statements in Section 3	<p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled</p> <p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>Skin Sens. 1: H317 - May cause an allergic skin reaction.</p> <p>Eye Irrit. 2: H319 - Causes serious eye irritation.</p> <p>Acute Tox. 4: H312 - Harmful in contact with skin.</p> <p>Acute Tox. 4: H332 - Harmful if inhaled.</p> <p>STOT SE 3: H336 - May cause drowsiness or dizziness.</p> <p>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.</p> <p>STOT SE 3: H335 - May cause respiratory irritation.</p> <p>Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.</p>

Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Larseal Impregnation Part B

Revision 7

Revision date 2023-10-25

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Larseal Impregnation Part B
Other means of identification / UFI	UFI: 8G0T-5FVR-499M-9PH8.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC5] Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact); [ERC3] Formulation in materials;
--------------------	---

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	l.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number


Emergency telephone number	(00353) 01 809 2166
Company	National Poisons Centre of Ireland 8am-10pm 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Eye Dam. 1: H318; Acute Tox. 4: H332;
---	--

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Eye Dam. 1: H318 - Causes serious eye damage. Acute Tox. 4: H332 - Harmful if inhaled.

Larseal Impregnation Part B

Revision 7

Revision date 2023-10-25

2.2. Label elements

Precautionary Statement: Prevention	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ . P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7		50 - 60%	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;
Butan-1-ol	603-004-00-6	71-36-3	200-751-6		1 - 10%	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336;
1-Methoxy-2-propanol (1-Methoxypropan-2-ol)	603-064-00-3	107-98-2	203-539-1		10 - 20%	Flam. Liq. 3: H226; STOT SE 3: H336;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO ₂), Dry chemical, Foam.
--	--

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

Larseal Impregnation Part B

Revision 7
Revision date 2023-10-25

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

1-Methoxy-2-propanol (1-Methoxypropan-2-ol)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 375
	WEL 15 min limit ppm: 150	WEL 15 min limit mg/m3: 560
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Butan-1-ol	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 154
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Larseal Impregnation Part B

Revision 7

Revision date 2023-10-25

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless to straw yellow
Odour	Characteristic
pH	Not relevant
Initial boiling point	Not determined
Flash point	Not determined
Upper Explosive Limit	Not determined
Lower Explosive Limit	Not determined
Vapour pressure	Not determined
Relative Vapour Density	Not determined
Partition coefficient (n-octanol/water)	Not determined
Autoignition temperature	Not determined
Decomposition temperature	Not determined
Viscosity	Not relevant

9.2. Other information

Specific gravity	0.88 - 0.98 g/cm ³
VOC (Volatile organic compounds)	Not determined

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity	Harmful if inhaled.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitisation	Harmful if inhaled.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met).

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Hazard pictograms

Larseal Impregnation Part B

Revision 7

Revision date 2023-10-25

Hazard pictograms



14.1. UN number

UN1307

14.2. UN proper shipping name

XYLENES

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-D
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> 1 - Other means of identification / UFI. 9 - 9.1. Information on basic physical and chemical properties (PH). 9 - 9.1. Information on basic physical and chemical properties (Initial boiling point). 9 - 9.1. Information on basic physical and chemical properties (Flash point). 9 - 9.1. Information on basic physical and chemical properties (Autoignition temperature). 9 - 9.1. Information on basic physical and chemical properties (Vapour pressure). 9 - 9.1. Information on basic physical and chemical properties (Viscosity).
----------	--

Larseal Impregnation Part B

Revision 7

Revision date 2023-10-25

Other information

	<p>9 - 9.1. Information on basic physical and chemical properties (Relative Vapour Density). 9 - 9.1. Information on basic physical and chemical properties (Upper Explosive Limit). 9 - 9.1. Information on basic physical and chemical properties (Lower Explosive Limit). 9 - 9.1. Information on basic physical and chemical properties (Decomposition temperature). 9 - 9.1. Information on basic physical and chemical properties (Partition coefficient (n-octanol/water)). 9 - 9.2. Other information (Product Subcategory). 9 - 9.2. Other information (Specific gravity). 11 - Acute toxicity. 11 - Skin corrosion/irritation. 11 - Respiratory or skin sensitisation. 11 - Germ cell mutagenicity. 11 - Carcinogenicity. 11 - Reproductive toxicity. 11 - Serious eye damage/irritation. 11 - STOT-single exposure. 11 - STOT-repeated exposure. 16 - Maximum content of VOC.</p>
Text of Hazard Statements in Section 3	<p>Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Acute Tox. 4: H332 - Harmful if inhaled. Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.</p>

Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---