

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

Stain Resistant Wide Joint

Revision 2 Revision date 2017-08-30

1.1. Product identifier

1.2. Relevant identified uses of the substance or mixture and uses advised against				
Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC5] Industrial use resulting in inclusion into or onto a matrix; [AC4] Stone, plaster, cement, glass and ceramic articles;			
Description	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be mixed at the point of use with water for use in the construction industry.			

1.3. Details of the supplier of the safety data sheet

Address 4 West Bank Road

Belfast Harbour Industrial Estate

Belfast BT3 9JL United Kingdom

www.larsenbuildingproducts.com

Telephone +44 (0)28 9077 4000 Fax +44 (0)28 9077 6945

Email t.moore@larsenbuildingproducts.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification -	Xi; R36/37/38
1999/45/EC	Symbols: Xi: Irritant.

Main hazards Irritating to eyes, respiratory system and skin. 2.1.2. Classification - EC

1272/2008

Web

Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H335;

2.2. Label elements

Hazard pictograms





Signal Word

Hazard Statement

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Powered by

ChemSoft EH&S

Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation.

Revision 2 Revision date 2017-08-30

2.2. Label elements

Precautionary Statement:	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
Prevention	P264 - Wash thoroughly after handling.
	P271 - Use only outdoors or in a well-ventilated area.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .
Response	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
	P310 -Immediately call a POISON CENTER/doctor/ .
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.
	P321 - Specific treatment (see on this label).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Precautionary Statement:	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
Storage	P405 - Store locked up.
Precautionary Statement:	P501 - Dispose of contents/container to
Disposal	

Further information

This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Portland Cement		65997-15-1	266-043-4			Xi; R36/37/38	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc.	Classification	M-factor.
				Number	(%w/w)		
Portland Cement		65997-15-1	266-043-4			Skin Irrit. 2: H315; Skin Sens.	
						1: H317; Eye Dam. 1: H318;	
						STOT SE 3: H335;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.



Revision 2 Revision date 2017-08-30

5.3. Advice for firefigh	iters
--	-------

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Appropriate dedicated workwear is generally sufficient under normal handling conditions.

Eye / face protection

Suitable eye protection.

Skin protection -

Wear suitable gloves.

Handprotection

After contact with skin, wash immediately with plenty of water.

Skin protection - Other Respiratory protection

Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Suitable half mask respirator with filter P2 (EN 143). Suitable half mask respirator with filter P3 (EN

143).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Various
Solubility	Slightly miscible in water

SECTION 10: Stability and reactivity



Revision 2 Revision date 2017-08-30

10.1. Reactivity	
	Avoid contact with: Strong acids. Avoid contact with: Strong bases.
10.2. Chemical stability	·
	Stable under normal conditions.
10.3. Possibility of hazardous re	actions
	Organic materials.
10.4. Conditions to avoid	·
	Heat, sparks and open flames.
Further information	
	Avoid formation of dust.
SECTION 11: Toxicological	information
11.1. Information on toxicologica	
Acute toxicity	Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
Serious eye damage/irritation	Acute effect.
Respiratory or skin sensitisation	May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May produce an allergic reaction.
11.1.4. Toxicological Information	
	No data available
SECTION 12: Ecological info	ormation
12.1. Toxicity	
	No data available
Further information	
	No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.
SECTION 13: Disposal cons	iderations
General information	
	Dispose of in compliance with all local and national regulations. Eurpoean Waste Catalogue:. 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.
Disposal methods	
	Do not empty into drains; dispose of this material and its container in a safe way.
SECTION 14: Transport info	rmation
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es)	
	The product is not classified as dangerous for carriage.
14.4. Packing group	•
	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	•



Revision 2 Revision date 2017-08-30

14.5. Environmental hazards		
	The product is not classified as dangerous for carriage.	
14.6. Special precautions for user		
	The product is not classified as dangerous for carriage.	
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		
	The product is not classified as dangerous for carriage.	
Further information		
	The product is not classified as dangerous for carriage.	
SECTION 15: Regulatory information		

SECTION 16: Other information		
Other information		
Text of risk phrases in Section 3	R36/37/38 - Irritating to eyes, respiratory system and skin.	
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	

