VERSION: 01 ISSUED: JAN 2025

LARSEN BUILDERS MERCHANTS

TECHNICAL DATA SHEET

Line Marking Paint

EASY TO APPLY

ROAD MARKING SYSTEM

FAST DRYING

HIGH COLOUR PIGMENT

UV STABLE

Larsen Line Marking Paint is a blend of high quality pigments, resins, hardeners and fast-drying solvents, supplied in an easy to use aerosol dispenser. Larsen Line Marking Paint can be applied both by hand as a spot marker or used in conjunction with a line marking applicator. It is available in a range of colours.





For further information, consult our Technical Department. Belfast 028 9077 4000 Birmingham 028 9053 5409 Dublin 01 8348255 LarsenBuildingProducts.com



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET

PRODUCT INFORMATION

FORM	Aerosol Paint
COLOURS	White, Yellow, Red, Blue, Green
HAZARD INFORMATION	IRRITANT- Flammable - Consult Safety Datasheet before use.
CLEANING	May be cleaned off most surfaces and tools with thinners etc. Mechanical means are necessary when the product has set.
PACKAGING	750ml Aerosol cans
STORAGE CONDITIONS	Store in sealed containers protected from extremes of temperature (not greater than 50°C), out of direct sunlight and away from sources of ignition. Do not pierce or burn even after use.
SHELF LIFE	Minimum 36 months in unopened manufacturer's packaging in good storage

APPLICATION INFORMATION

TOUCH DRY	30 min
FULL CURE	24 hours
COVERAGE	75 – 100 metres x 50 mm width

DIRECTIONS FOR USE

PREPARATION

Ensure all substrates are clean and free from contamination. Substrates must be completely dry.

DIRECTIONS

Shake can vigorously until shaker balls move, then shake for a further 30 seconds. The nearer the aerosol spray is to the ground, the more accurate and denser the line. After use, clear the nozzle by spraying in the upright position.

Apply by hand as a spot marker or in conjunction with a line marking applicator.

IMPORTANT NOTE

Line Marking Paint is IRRITANT and EXTREMELY FLAMMABLE – Consult container and/or MSDS before use.

The information and recommendations above are given in good faith based on our current knowledge and experience of the products when properly stored, handled, and applied in accordance with current best practice, national standards, and our recommendations. As we have no control over site conditions or methods of application, no liability can be derived from the contents of this information sheet, or from any written recommendations, or from any other advice offered. The user of the product is solely responsible for the product's suitability for the intended application and is recommended to test the suitability prior to use. We reserve the right to change the properties of our products without notice. All orders are sold subject to our current terms of sale and delivery. With the publication of this Technical Information Sheet all previous editions are no longer valid.