

LARSEN**BUILDERS MERCHANTS****TECHNICAL DATA SHEET**

Roofing Compound (Brush Grade)

EASY TO APPLY**READY TO USE****WATER-RESISTANT****UNAFFECTED BY RAIN OR
FROST IMMEDIATELY AFTER
APPLICATION**

Roofing Compound (Brush Grade) is a solvent-based, Fibre and mineral filler modified bitumen solution used to provide excellent protection to roof structures. It is ideal for use on flat roofs and gutter repairs and is weatherproof and frost resistant immediately after application.



HA **HARDWARE
ASSOCIATION
IRELAND**
The voice of the Irish Hardware Industry

TECHNICAL DATA SHEET

PRODUCT INFORMATION

FORM	Black Paste
MATERIAL	Thick Bodied Bituminous Paint
PACKAGING	2.5L and 5L metal paint tins
CLEANING	Tools and spillages should be cleaned with white spirit.
STORAGE CONDITIONS	Store in manufacturer's containers in a cool, dry, well ventilated and frost-free place out of direct sunlight.
SHELF LIFE	12 months in manufacturer's unopened containers.
FLASH POINT	39°C
WATER RESISTANCE	Resistant to water when dried
COVERAGE	1.5 m ² /L/coat

DIRECTIONS FOR USE

PREPARATION

Surfaces should be dry, clean, and free from grease, dust and loose debris. Lichen and moss should be removed and the surface treated with Larsen Concentrated Algicide. Cracks, breaks, open-seamed blisters, loose and torn flashings should be treated with Larsen Roofing Compound Trowel Grade prior to application.

APPLICATION

Do not thin. Mix well before use. Apply 2 coats by brush at a rate of 1.5m² per coat applying the second coat after the first has dried. On large areas embed bitumised glass fibre scrim or hessian in to the first coat while still wet.

RESTRICTIONS

Keep away from sources of ignition - no smoking. Use only in well ventilated areas. Avoid contact with eyes. Wash splashes off skin. Keep out of reach of children. Consult MSDS before use. Do not apply over tar based surfaces or surfaces that can rise above 65°C.