

VERSION: 01

ISSUED: NOV 2024

LARSEN

TILING

TECHNICAL DATA SHEET

Impregnating Sealer

**ADVANCED IMPREGNATOR
FOR POROUS TILES**

**PROVIDES A WATER
REPELLENT SEAL**

**ENHANCES COLOUR OF
TREATED SURFACE**

Impregnating Sealer is an advanced, solvent based surface protector and colour enhancer. It is ideal for providing a water repellent, stain resistant seal to slate and porous tiles, while improving and intensifying colour.



For further information, consult our Technical Department.

LarsenBuildingProducts.com

Belfast 028 9077 4000 Birmingham 028 9053 5409 Dublin 01 8348255



TECHNICAL DATA SHEET

PRODUCT INFORMATION

FORM:	Liquid
COLOUR:	Colourless
HAZARD INFORMATION:	FLAMMABLE – Consult Safety Datasheet before use. Contains: White Spirit VOC content less than 750g/L
CLEANING:	Clean tools, equipment, etc. using warm water.
PACKAGING:	1L Plastic Containers
STORAGE INSTRUCTIONS	Store in sealed containers in dry conditions, protected from extremes of temperature
SHELF LIFE	12 months in unopened manufacturer's packaging

APPLICATION INFORMATION

APPLICATION TEMPERATURE:	+3°C to +30°C
COVERAGE:	2-10 m ² /L depending on dilution
EXPECTED LIFE:	3-5 years depending on traffic, etc.

DIRECTIONS FOR USE

NOTE

While Impregnating Sealer is suitable for almost all porous surfaces, it is recommended to always test on an inconspicuous area first to ensure suitability for use. Particular care should be taken to protect the surrounding surfaces.

SUITABILITY Suitable for use on slate, quarry tiles, certain types of natural stone, unglazed ceramics and cement based grout.

DIRECTIONS

Supplied ready for use, do not further dilute. Surface to be treated should be clean, free from staining and contamination. Any existing stains will be almost impossible to remove following treatment. If the floor has been cleaned recently allow surface to dry for 3 days. (Underfloor heating should be switched off 24 hours prior to application.) Apply in a thin layer uniformly with a cloth, brush or sponge and allow to penetrate for approximately 15-30 minutes. Then remove all excess product from the surface with a clean lint-free cloth. Very porous surfaces may require further treatments as above. Should any product remain on the surface, remove by further buffing with a clean cloth. Surface can be walked on after 6 hours and fully trafficked after 2-3 days.