

# MULTI PURPOSE SILICONE



Larsen Multi Purpose Silicone is a one part versatile elastic sealant based on polysiloxanes for sealing building joints and glazing systems. After application Multi Purpose cures with atmospheric moisture to provide a durable, waterproof elastic seal with excellent adhesion to glass, ceramics, enamel and porcelain. It is ideal for joints in brickwork; around doors and windows; around sanitary-ware; and cap beading.



**MULTI PURPOSE  
SILICONE SEALANT  
ACETOXY SILICONE SEALANT  
LOW-SHRINK  
±25% MOVEMENT CAPABILITY  
EXCELLENT ADHESION**

**TECHNICAL INFORMATION:**

PRODUCT INFORMATION		
<b>FORM:</b>	Paste	
<b>COLOURS:</b>	Clear, White, Brown, Grey Black	
<b>SPECIFIC GRAVITY:</b>	0.94 g/ml	
<b>MOVEMENT:</b>	+/-25%	
<b>SKINNING TIME:</b>	5 - 10 min @ 20°C	
<b>APPLICATION TEMP.:</b>	+ 5 to + 30°C	
<b>TEMP. RESISTANCE:</b>	-50 to + 120°C	
<b>HARDNESS SHORE A:</b>	10	
<b>100% MODULUS:</b>	0.15 MPa	
<b>ELONGATION AT BREAK:</b>	800%	
<b>MINIMUM JOINT WIDTH:</b>	4 mm	
<b>MAXIMUM JOINT WIDTH:</b>	25 mm	
<b>COVERAGE:</b>	<b>Joint</b> 5x5mm 10x10mm 10x20mm	<b>Linear Metres / Cartridge</b> 11 3 1.5

## **DIRECTIONS FOR USE:**

### **PREPARATION**

Surfaces to be sealed must be clean, dry, sound and free from dust, oil or grease. Primer is not required on clean glass, ceramics and enamelled surfaces.

### **APPLICATION**

Remove cartridge tip with a sharp knife. Cut nozzle to required size and angle. Using a skeleton gun, apply sealant continuously, ensuring full contact with all surfaces. Multipurpose Silicone should be tooled within five minutes. Soapy water will assist finishing process.

### **RESTRICTIONS**

Multipurpose Silicone cannot be over-painted. It is not recommended for aquaria, on concrete, marble, lead, copper, galvanized steel and not for PE, PP, Teflon and bituminous or wax containing surfaces. It is not recommended for direct contact with the perimeter of isolation glass and the edges of laminated safety glass. Adhesion tests prior to application are recommended. It is the user's responsibility to determine suitability.

### **CLEANING**

Clean tools directly after use with white spirit; wash hands with soap and hot water.

### **STORAGE**

Store in manufacturer's containers in a cool, dry, and frost-free place.

### **SHELF LIFE**

12 months in manufacturer's unopened containers.

### **PACKAGING**

290ml cartridges.