

# SAFETY DATA SHEET according to Regulation (EU) 2020/878

# Stain Repel

Page 1/5

Revision 10 Revision date 2023-11-22

SECTION 1: Identification of	the substance/mixture and of the company/undertaking		
1.1. Product identifier			
Product name	Stain Repel		
Other means of identification /	UFI: VQKK-NMSY-MA9K-NH7N.		
UFI			
1.2. Relevant identified uses of t	he substance or mixture and uses advised against		
Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC10] Roller application or brushing; [ERC5] Industrial use resulting in inclusion into or onto a matrix;		
1.3. Details of the supplier of the	e safety data sheet		
Company	Larsen Building Products Ltd		
Address	4 West Bank Road		
	Belfast Harbour Industrial Estate		
	Belfast BT3 9JL		
	United Kingdom		
Web	www.larsenbuildingproducts.com		
Telephone	+44 (0)28 9077 4000		
Fax	+44 (0)28 9077 6945		
Email	l.pyper@larsenbuildingproducts.com		
1.4. Emergency telephone numb	ber		
Emergency telephone number	(00353) 01 809 2166		
Company	National Poisons Centre of Ireland		
	8am-10pm 7 days a week		
SECTION 2: Hazards identif	ication		
2.1. Classification of the substar	nce or mixture		
2.1.2. Classification - EC	Flam. Liq. 3: H226; Asp. Tox. 1: H304;		
1272/2008			
2.2. Label elements			
Hazard pictograms			
Signal Word	Danger		
Hazard Statement	Flam. Liq. 3: H226 - Flammable liquid and vapour.		
	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.		
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No		
	smoking. P233 - Keep container tightly closed.		



# **Stain Repel**

2.2. Label elements	
Precautionary Statement: Response	<ul> <li>P240 - Ground/bond container and receiving equipment.</li> <li>P241 - Use explosion-proof electrical/ventilating/lighting// equipment.</li> <li>P242 - Use only non-sparking tools.</li> <li>P243 - Take precautionary measures against static discharge.</li> <li>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ .</li> <li>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</li> <li>P331 - Do NOT induce vomiting.</li> <li>P370+P378 - In case of fire: Use to extinguish.</li> </ul>
Precautionary Statement: Storage Precautionary Statement:	P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to comply with local and national regulations
Disposal	

# SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	649-405-00-X	64742-88-7	265-191-7		90 - 100%	Asp. Tox. 1: H304;
Silicone Resin					1 - 10%	Flam. Liq. 3: H226; Asp. Tox.
						1: H304; Eye Irrit. 2: H319;
						STOT SE 3: H336;

# SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

# SECTION 5: Firefighting measures

# 5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.	
5.2. Special hazards arising from the substance or mixture		
	Burning produces irritating, toxic and obnoxious fumes.	
5.3. Advice for firefighters		
	Self-contained breathing apparatus. Wear protective clothing.	
SECTION 6: Accidental release measures		

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

#### 6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.



# Revision 10

Revision date 2023-11-22

#### 6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

## SECTION 8: Exposure controls/personal protection

#### 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection	Wear chemical protective clothing.
measures	
Eye / face protection	Approved safety goggles.
Skin protection -	Chemical resistant gloves (PVC).
Handprotection	
Respiratory protection	Wear protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
	Colourless to straw yellow
Odour	Characteristic
pH	No data available
Initial boiling point	168 °C
Flash point	48 °C
Upper Explosive Limit	6.4 %
Lower Explosive Limit	0.9 %
Vapour pressure	230 Pa
Relative Vapour Density	No data available
Partition coefficient	No data available
Autoignition temperature	515 °C
Decomposition temperature	No data available
Viscosity	No data available
Solubility	Slightly soluble in water

#### 9.2. Other information

Specific gravity	0.88 g/cm <sup>3</sup>
VOC (Volatile organic	No data available
compounds)	

# SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes



Revision date 2023-11-22

# 11.1 Information on hazard classes

Acute toxicity	May be fatal if swallowed and enters airways.
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met).
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met).
Respiratory or skin	May cause sensitisation by inhalation. May cause sensitisation by skin contact. May cause
sensitisation	drowsiness or dizziness.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
STOT-repeated exposure	Repeated exposure may cause skin dryness or cracking.

#### 11.1.4. Toxicological Information

No data available

## **SECTION 12: Ecological information**

12.1. Toxicity

No data available

12.3. Bioaccumulative potential

## Partition coefficient

Stain Repel No data available

## SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

## SECTION 14: Transport information

#### Hazard pictograms



14.1. UN number

	UN1300
14.2. UN proper shipping name	

	TURPENTINE SUBSTITUTE		
14.3. Transport hazard class(es)			
ADR/RID	3		
Subsidiary risk	-		
IMDG	3		
Subsidiary risk	-		
ΙΑΤΑ	3		
Subsidiary risk	-		
14.4. Packing group			
Packing group	Ш		



14.5. Environmental hazards		
Environmental hazards	No	
Marine pollutant	No	
ADR/RID		
Hazard ID	30	
Tunnel Category	(D/E)	
IMDG		
EmS Code	F-E S-E	
ΙΑΤΑ		
Packing Instruction (Cargo)	366	
Maximum quantity	220 L	
Packing Instruction	355	
(Passenger)		
Maximum quantity	60 L	
SECTION 15: Regulatory information		

# SECTION 16: Other information

Other information	
Revision	This document differs from the previous version in the following areas:. 2 - Precautionary Statement: Disposal.
Text of Hazard Statements in Section 3	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Flam. Liq. 3: H226 - Flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

