

MOULD RELEASE AGENT 'D'

Larsen Mould Release Agent 'D' is a chemical release agent. It has been specifically formulated to provide easy release of formwork and to provide high quality surface finishes to concrete (including concrete produced with white cements). Mould Release Agent 'D' is suitable for use on steel, plywood, timber, G.R.P., and synthetic formwork or moulds. The use of Mould Release Agent 'D' results in greatly reduced incidence of blow holes, staining and surface blemishes.

SUITABLE ON ALL TYPES OF FORMWORK
ECONOMICAL COVERAGE RATES
PLEASANT ODOUR
DRIES IN 1-2 HOURS
EASY TO APPLY
FOR HIGH QUALITY WHITE OR GREY CONCRETE

TECHNICAL INFORMATION

FORM: Liquid

COLOUR: Red / Brown

SPECIFIC GRAVITY: 0.8 g/ml

SOLUBILITY: Insoluble in water. Soluble in white spirits (and similar organic solvents)

FLASH POINT: 38°C

COVERAGE: Dependent on application. Approx. 25-50 m²/L

DIRECTIONS FOR USE:

PREPARATION

Formwork should be clean and dry.

DIRECTIONS

Mould Release Agent 'D' is supplied ready for use and should not be diluted, as this will seriously affect the properties. Apply a thin and even coat, preferably by spray. When using Mould Release Agent 'D' on unsealed timber formwork, a sealing coat should be applied, followed by a second coat prior to placing concrete. Any excess should be mopped up. Protect from rain until dry (1-3 hours depending on conditions). For best results and highest economy, apply Mould Release Agent 'D' by spray. 9L spray units are available ex stock for this application.

CLEANING

Clean tools, equipment, etc. using white spirit before the product has dried.

STORAGE

Mould Release should be stored in closed containers protected from extremes of temperature and sources of ignition.

SHELF LIFE

12 months in unopened manufacturer's containers.

PACKAGING

Mould Release Agent 'D' is supplied in 5L, 25L, 200L and bulk deliveries.