

PAINTER'S CAULK



Painter's Caulk is an easy to use, low odour, acrylic sealant ideal for internal or external use. It is ideal for sealing joints between skirting, architrave, stairs and walls, around windows and window sills and where limited movement occurs prior to decorating. Easy to apply it gives a smooth finish which doesn't require sanding before painting. Painter's Caulk can be painted with water based (emulsion) paints after as little as 1 hour.

FLEXIBLE FILLER
INTERIOR & EXTERIOR
PAINT AFTER 1 HR
SMOOTH FINISH
WHITE



TECHNICAL INFORMATION:

PRODUCT INFORMATION									
FORM:	Paste								
COLOUR:	White								
MATERIAL:	Acrylic emulsion filler								
HAZARD INFORMATION:	Generally non-hazardous in normal use - consult safety datasheet before use								
CLEANING:	Clean tools, equipment etc. using water. Mechanical means are necessary when the product has set.								
PACKAGING:	310ml and 400ml Silicone Cartridges								
STORAGE CONDITIONS:	Store in sealed containers in dry conditions, protected from extremes of temperature								
SHELF LIFE:	12 months in unopened manufacturer's packaging								
APPLICATION INFORMATION									
SPECIFIC GRAVITY:	1.72 g/ml								
MOVEMENT:	+/-7.5%								
SKINNING TIME:	5 - 10 min @ 20°C								
OVERPAINTING:	Emulsion paints after 1-2hours								
APPLICATION TEMP.:	+ 5 to + 40°C								
TEMP. RESISTANCE:	-20 to + 70°C								
HARDNESS SHORE A:	40								
100% MODULUS:	0.5 MPa								
ELONGATION AT BREAK:	250%								
CLASSIFICATION:	ISO 11600 F-7.5								
MAXIMUM JOINT WIDTH:	25 mm								
COVERAGE:	<table border="0"> <thead> <tr> <th>Joint</th> <th>Linear Metres / 310ml Cartridge</th> </tr> </thead> <tbody> <tr> <td>6x6mm</td> <td>8.6</td> </tr> <tr> <td>12x8mm</td> <td>3.2</td> </tr> <tr> <td>12x20mm</td> <td>1.3</td> </tr> </tbody> </table>	Joint	Linear Metres / 310ml Cartridge	6x6mm	8.6	12x8mm	3.2	12x20mm	1.3
Joint	Linear Metres / 310ml Cartridge								
6x6mm	8.6								
12x8mm	3.2								
12x20mm	1.3								

DIRECTIONS FOR USE:

PREPARATION

The surface must be clean and totally dust-free, can be applied to slightly damp surfaces.

In deep or through joints, reduce the joint depth by using a polyethylene backing material or Larsen Easy Foam sealant.

APPLICATION

Used for the sealing and filling of gaps and cracks where limited movement can occur. Primer is not required generally required.

Remove cartridge tip with a sharp knife. Cut nozzle to required size and angle. Using skeleton gun, apply sealant continuously, ensuring full contact with all surfaces. Must be tooled within five minutes. Finish with a filling knife or paint scraper. Soapy water will assist finishing process.

RESTRICTIONS

Among others not recommended for continuous water immersion and not for sealing PE, PP, Teflon and bituminous surfaces. Painting over with highly filled emulsion paints may result in cracks in the paint film. When painting with solvent based paints allow sealant to dry for at least 24hours first. When using externally ensure good drying conditions and protect from damp until fully cured. It is the user's responsibility to determine suitability for use. Painter's Caulk cures by loss of moisture, therefore curing will be slowed in cold or damp applications and on non-porous or painted surfaces.