

# LARDEC



Lardec is a solvent-based, long-chain, alkyd wood stain and primer. It is ideal for use on all joinery components; for example, window frames, doors, garden sheds and garden furniture, poultry houses, etc. Lardec will not peel or flake and can be over-painted. It has excellent penetration and 'run off' properties and won't obscure the grain. Lardec is also available in a higher resin-solids version (Lardec 24) for improved performance.



**PRIMING WOOD STAIN**  
**READY TO USE**  
**EASY TO APPLY**  
**RANGE OF STANDARD COLOURS**

**TECHNICAL INFORMATION:**

PRODUCT INFORMATION	
<b>FORM:</b>	Solvent-based alkyd primer
<b>COLOURS:</b>	Redwood, Pine, Teak, Ebony
<b>SPECIFIC GRAVITY:</b>	0.85 g/ml
<b>FLASH POINT:</b>	36°C
<b>DRYING TIME @ 20°C:</b>	<u>Touch Dry:</u> 2 hrs <u>Hard Dry:</u> 8 hrs
<b>MIN. APPLICATION TEMP.:</b>	5°C (for 36 hrs)
<b>COVERAGE:</b>	1L will cover 5-10 m <sup>2</sup> (depending on timber)

## **DIRECTIONS FOR USE:**

### **PREPARATION**

Sand surface lightly. Surfaces must be clean, dry, and free from dust and grease.

### **APPLICATION**

Ready to use - do not dilute. Mix well before use. Always check colour before use. Brush or spray apply. Alternatively, a dip tank system may be used.

### **CAUTION**

Ensure adequate ventilation during application and curing. Avoid naked flames - flammable. Do not apply to wet surfaces, in conditions of high humidity or when rain is forecast. Protect from rain until dry. No smoking during application. If in doubt, contact our Technical Department.

### **CLEANING**

Clean tools, equipment, etc. using white spirit or proprietary brush cleaner.

### **STORAGE**

Lardec should be stored in closed containers protected from extremes of temperature. Partially used packs may develop a skin on storage.

### **SHELF LIFE**

12 months in unopened manufacturer's containers.

### **PACKAGING**

2.5L, 5L, 25L and 200L packs.