

VERSION: 01

ISSUED: JAN 2025



LARSEN

ADMIXTURES

TECHNICAL DATA SHEET

Cement Colours

EASY TO USE

AVAILABLE IN 4 COLOURS

RE-SEALABLE PACKS

Larsen Cement Colours are concentrated powder pigments for use with any cementitious mix. They are suitable for use in coloured mortars, renders, concrete mixes, grouts and pointing. Larsen Cement Colours are supplied in easy to use resealable packs.



HA **HARDWARE**
ASSOCIATION
IRELAND
The voice of the Irish Hardware Industry

For further information, consult our Technical Department.

Belfast 028 9077 4000 Birmingham 028 9053 5409 Dublin 01 8348255

LarsenBuildingProducts.com



TECHNICAL DATA SHEET

PRODUCT INFORMATION

FORM	Powder
COLOURS	Black, Red, Brown, Yellow
SPECIFIC GRAVITY	~1.01g/ml
CHLORIDE CONTENT	Nil (i.e. <0.2 %)
DOSAGE	2% by weight of cement

DIRECTIONS FOR USE

APPLICATION

Add the required amount of pigments to the dry aggregates. Allow to mix for about one minute, and then add water. Allow 1kg of pigment per 50kg cement for standard shades. Lighter colours may require the use of white cement. Test before use with Lime mortars. Treat as standard mortar or concrete with regards to curing, etc. Efflorescence is a natural phenomenon which can cause the apparent lightening of coloured cement. Efflorescence generally weathers away after about 1 year. The effects of efflorescence can be reduced by the inclusion of a waterproofer in the mix.

CLEANING

Clean tools with clean water.

STORAGE

Store in a cool, dry place in closed containers.

SHELF LIFE

12 months in unopened manufacturer's containers.

PACKAGING

0.5kg and 1kg tubs