

# SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

## Fusion XT Priming Slurry

Revision 14

Revision date 2024-05-29

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	Fusion XT Priming Slurry
Other means of identification / UFI	UFI: 3XJA-X3AF-CNKT-8GV4.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Description	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be mixed at the point of use with water for use in the construction industry.
-------------	---

#### 1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	l.pyper@larsenbuildingproducts.com

#### 1.4. Emergency telephone number


Emergency telephone number	(00353) 01 809 2166
Company	National Poisons Centre of Ireland 8am-10pm 7 days a week

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
--------------------------------------	--

#### 2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage.
Precautionary Statement: Prevention	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace.

# Fusion XT Priming Slurry

Revision 14  
Revision date 2024-05-29

## 2.2. Label elements

<b>Precautionary Statement: Response</b>	P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ . P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
<b>Precautionary Statement: Disposal</b>	P501 - Dispose of contents/container to comply with local and national regulations

## Further information

	This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.
--	---

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Portland Cement		65997-15-1	266-043-4		30 - 40%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
Calcium Hydroxide		1305-62-0	215-137-3		1 - 10%	Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H335;

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Inhalation</b>	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
<b>Eye contact</b>	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
<b>Skin contact</b>	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
<b>Ingestion</b>	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Carbon oxides.
--	----------------

### 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

### 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

### 6.3. Methods and material for containment and cleaning up

# Fusion XT Priming Slurry

Revision 14  
Revision date 2024-05-29

## 6.3. Methods and material for containment and cleaning up

Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## 6.4. Reference to other sections

See section 2, 8, 13 for further information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

### 7.3. Specific end use(s)

See section 1.2. Relevant identified uses of the substance or mixture and uses advised against for further information.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Occupational exposure controls.

#### 8.1.1. Exposure Limit Values

Calcium Hydroxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 5
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -
Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total inhalable dust: 10	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: 4	WEL 15 min limit mg/m3 total respirable dust: -

### 8.2. Exposure controls



#### 8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

#### 8.2.2. Individual protection measures

Appropriate dedicated workwear is generally sufficient under normal handling conditions.

#### Eye / face protection

Suitable eye protection.

#### Skin protection - Handprotection

Wear suitable gloves.

#### Skin protection - Other

After contact with skin, wash immediately with plenty of water.

#### Respiratory protection

Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9: Physical and chemical properties

## Fusion XT Priming Slurry

Revision 14  
Revision date 2024-05-29

## 9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Grey
pH	Not applicable.
Initial boiling point	Not applicable.
Flash point	Not applicable.
Upper Explosive Limit	Not applicable.
Lower Explosive Limit	Not applicable.
Vapour pressure	Not applicable.
Relative Vapour Density	Not applicable.
Partition coefficient (n-octanol/water)	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Solubility	Slightly soluble in water

## 9.2. Other information

Bulk Density	1.1 - 1.3 g/cm <sup>3</sup>
VOC (Volatile organic compounds)	Not applicable.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

	Avoid contact with: Strong acids. Avoid contact with: Strong bases.
--	---

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.3. Possibility of hazardous reactions

	Organic materials.
--	--------------------

## 10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

## Further information

	Avoid formation of dust.
--	--------------------------

## SECTION 11: Toxicological information

## 11.1 Information on hazard classes

Acute toxicity	Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May produce an allergic reaction.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
Aspiration hazard	Not classified (Based on available data, the classification criteria are not met).
Repeated or prolonged exposure	Not classified (Based on available data, the classification criteria are not met).

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## Fusion XT Priming Slurry

Revision 14

Revision date 2024-05-29

## 11.2 Information on other hazards

No data available.

## SECTION 12: Ecological information

## 12.1. Toxicity

No data available

## Further information

No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

Contact a licensed waste disposal company.

## General information

Dispose of in compliance with all local and national regulations. European Waste Catalogue: 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.

## Disposal methods

Do not empty into drains; dispose of this material and its container in a safe way.

## SECTION 14: Transport information

## Further information

The product is not classified as dangerous for carriage.

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Regulations

COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

## 15.2. Chemical safety assessment

No data is available on this product.

## SECTION 16: Other information

## Other information

## Revision

This document differs from the previous version in the following areas:  
2 - Hazard pictograms.

## Text of Hazard Statements in Section 3

Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
Eye Dam. 1: H318 - Causes serious eye damage.  
STOT SE 3: H335 - May cause respiratory irritation.

## Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information

# Fusion XT Priming Slurry

Revision 14

Revision date 2024-05-29

---

**Further information**

---

	relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	---

---