

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/5

Streetscape GPM Eco

Revision q Revision date 2023-11-22

SECTION 1: Identification of the substance/mixture and o	of the company/undertaking
--	----------------------------

1.1. Product identifier

Product name
Other means of identification /
UFI

Streetscape GPM Eco

UFI: SXVQ-5RH9-R99J-WNGN.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be
	mixed at the point of use with water for use in the construction industry.

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
---------	------------------------------

Address 4 West Bank Road

Belfast Harbour Industrial Estate

Belfast BT3 9JL United Kingdom

Web www.larsenbuildingproducts.com

Telephone +44 (0)28 9077 4000 Fax +44 (0)28 9077 6945

Email I.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number

Emergency telephone number

(00353) 01 809 2166

National Poisons Centre of Ireland Company

8am-10pm 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - E0	3
1272/2008	

Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;

2.2. Label elements





Signal Word

Hazard Statement

Danger

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Eye Dam. 1: H318 - Causes serious eye damage.

Precautionary Statement:

Prevention

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

Revision 9 Revision date 2023-11-22

^	^	- 1-	- 1	- 1	l			. 4 .
~	2	 ar	וםי		Δľ	n	۵n	ìΤC

	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .
Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
	P310 -Immediately call a POISON CENTER/doctor/ .
	P321 - Specific treatment (see on this label).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Precautionary Statement:	P501 - Dispose of contents/container to comply with local and national regulations
Disposal	
E 0	

Further information

This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4		60 - 70%	
Portland Cement		65997-15-1	266-043-4		20 - 30%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
Calcium Formate		544-17-2			1 - 10%	5 Eye Dam. 1: H318;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

Revision 9
Revision date 2023-11-22

6.3. Methods and material for containment and cleaning up

Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Silica Sand (<1% Respirable Quartz)	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 0.1
·	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total
	respirable dust:	respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection	Appropriate dedicated workwear is generally sufficient under normal handling conditions.
measures	
Eye / face protection	Suitable eye protection.
Skin protection -	Wear suitable gloves.
Handprotection	
Skin protection - Other	After contact with skin, wash immediately with plenty of water.
Respiratory protection	Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Revision 9
Revision date 2023-11-22

9.1. Information on basic physical and chemical properties

Appearance Powder Colour Various Not applicable. pΗ Initial boiling point Not applicable. Flash point Not applicable. Upper Explosive Limit Not applicable. Lower Explosive Limit Not applicable. Vapour pressure Not applicable. **Relative Vapour Density** Not applicable. Partition coefficient Not applicable. (n-octanol/water) Decomposition temperature Not applicable. Viscosity Not applicable. Solubility Slightly soluble in water

9.2. Other information

Bulk Density
VOC (Volatile organic compounds)

1.4 - 1.6 g/cm³

Not applicable.

Water solubility

Miscible in water.

SECTION 10: Stability and reactivity

10.1. Reactivity

Avoid contact with: Strong acids. Avoid contact with: Strong bases.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Organic materials.

10.4. Conditions to avoid

Heat, sparks and open flames.

Further information

Avoid formation of dust.

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity
Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids
(e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

Acute effect.

Respiratory or skin
sensitisation

May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May produce an allergic reaction.

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

Revision 9 Revision date 2023-11-22

Further information	
	No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.
SECTION 13: Disposal cons	iderations
General information	
	Dispose of in compliance with all local and national regulations. Eurpoean Waste Catalogue:. 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.
Disposal methods	
	Do not empty into drains; dispose of this material and its container in a safe way.
SECTION 14: Transport info	rmation
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory inf	ormation

SECTION 16: Other information	
Other information	
Revision	This document differs from the previous version in the following areas:.
	2 - Precautionary Statement: Disposal.
Text of Hazard Statements in	Skin Irrit. 2: H315 - Causes skin irritation.
Section 3	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	Eye Dam. 1: H318 - Causes serious eye damage.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and

combination with any other materials or in any other process.

belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in