

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Quick Mix Leak Plug

Revision 10
Revision date 2026-04-22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Quick Mix Leak Plug
Other means of identification / UFI	FMPT-PFPD-G99C-0NMD.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC5] Industrial use resulting in inclusion into or onto a matrix;
Description	A factory produced drymix mortar (blend of sand, hydraulic binders, fillers and additives) to be mixed at the point of use with water for use in the construction industry.

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	l.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number


Emergency telephone number	(00353) 01 809 2166
Company	National Poisons Centre of Ireland 8am-10pm 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
---------------------------------------------	------------------------------------------------------------

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction.

Quick Mix Leak Plug

Revision 10
Revision date 2026-04-22

2.2. Label elements

Precautionary Statement: Prevention	Eye Dam. 1: H318 - Causes serious eye damage. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ . P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to appropriate waste disposal site

Further information

	This product contains portland cement which contains Chromium VI. Reducing agents have been added to this product to reduce the risk of allergic dermatitis when the product is mixed with water, providing the product has been stored as directed and is within its shelf life.
--	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Portland Cement		65997-15-1	266-043-4		40 - 50%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4		20 - 30%	
Sodium Bicarbonate refined (BP/EP/USP/FFQ)		144-55-8	205-633-8		10 - 20%	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335;
Sodium carbonate	011-005-00-2	497-19-8	207-838-8		1 - 10%	Eye Irrit. 2: H319;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---------------------------------------------------------

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---------------------------------------------------------------

SECTION 6: Accidental release measures

Quick Mix Leak Plug

Revision 10
Revision date 2026-04-22

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--------------------------------------------------------------------------------------

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	-------------------------------------------------------------------------

6.3. Methods and material for containment and cleaning up

	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	------------------------------------------------------------------------------------------------------------------------

6.4. Reference to other sections

	See section 2, 8, 13 for further information.
--	-----------------------------------------------

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--------------------------------------------------------------------------------------------------------------------

7.3. Specific end use(s)

	See section 1.2. Relevant identified uses of the substance or mixture and uses advised against for further information.
--	-------------------------------------------------------------------------------------------------------------------------

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

	Occupational exposure controls.
--	---------------------------------

8.1.1. Exposure Limit Values

Portland Cement	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Silica Sand (<1% Respirable Quartz)	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 0.1
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total
	respirable dust:	respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Appropriate dedicated workwear is generally sufficient under normal handling conditions.
Eye / face protection	Suitable eye protection.
Skin protection - Handprotection	Wear suitable gloves.
Skin protection - Other	After contact with skin, wash immediately with plenty of water.
Respiratory protection	Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Quick Mix Leak Plug

Revision 10

Revision date 2026-04-22

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	Powder
Colour	Grey
pH	11-13.5 (when water is added)
Initial boiling point	Not applicable.
Flash point	Not applicable.
Upper Explosive Limit	Not applicable.
Lower Explosive Limit	Not applicable.
Vapour pressure	Not applicable.
Relative Vapour Density	Not applicable.
Density / Relative Density	Not determined
Partition coefficient (n-octanol/water)	Not applicable.
Autoignition temperature	Not applicable.
Decomposition temperature	Not determined
Viscosity	Not applicable.
Solubility	Slightly miscible in water

9.2. Other information

VOC (Volatile organic compounds)	Not applicable.
-----------------------------------------	-----------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

	Avoid contact with: Strong acids. Avoid contact with: Strong bases.
--	---------------------------------------------------------------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Organic materials.
--	--------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

Further information

	Avoid formation of dust.
--	--------------------------

SECTION 11: Toxicological information**11.1 Information on hazard classes**

Acute toxicity	Irritating to eyes, respiratory system and skin. Contact between cement powder and body fluids (e.g. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause sensitisation by skin contact. Contains portland Cement (contains Chromium VI). May produce an allergic reaction.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met).
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
Aspiration hazard	Not classified (Based on available data, the classification criteria are not met).
Repeated or prolonged exposure	Not classified (Based on available data, the classification criteria are not met).

Quick Mix Leak Plug

Revision 10
Revision date 2026-04-22

11.1.4. Toxicological Information

No data available

11.2 Information on other hazards

No data available.

SECTION 12: Ecological information

12.1. Toxicity

No data available

Further information

No known adverse environmental effects. Do not allow product to enter drains. Do not flush into surface water.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact a licensed waste disposal company.

General information

Dispose of in compliance with all local and national regulations. Eurpoean Waste Catalogue:. 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10.

Disposal methods

Do not empty into drains; dispose of this material and its container in a safe way.

SECTION 14: Transport information

14.1. UN number

The product is not classified as dangerous for carriage.

14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

14.4. Packing group

The product is not classified as dangerous for carriage.

14.5. Environmental hazards

The product is not classified as dangerous for carriage.

14.6. Special precautions for user

The product is not classified as dangerous for carriage.

14.7 Maritime Transport in bulk according to IMO instruments

The product is not classified as dangerous for carriage.

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Quick Mix Leak Plug

Revision 10

Revision date 2026-04-22

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 1 - Other means of identification / UFI. 2 - Hazard pictograms.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H335 - May cause respiratory irritation.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------