

EXTERIOR WOODSTAIN & PRESERVER

A solvent-based, ready-to-use wood preservative for the treatment of new and existing timber.

It is a protective and decorative minimal build stain offering prevention of the effects of wood destroying and wood discolouring fungi and woodworm.

For application on all exterior timber, which is not in direct contact with the ground or surface water, e.g. joists, end grains, facades, windows, doors, fences, sheds etc.

Oil Based
2in1 Protection
Stain and Preservative
Prevents rot and woodworm
Long lasting protection



TECHNICAL INFORMATION

PRODUCT INFORMATION	
FORM:	Solvent based Liquid
COLOUR:	Pine, Mahogany, Teak, Fir Green
HAZARD INFORMATION:	WARNING. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects. UN 3082
CLEANING:	Clean tools immediately after use with a commercial brush cleaner or thinners
PACKAGING:	2.5L and 5L
STORAGE CONDITIONS:	Protect from frost and below 30°C. Store in a safe place away from food or feed stuffs.
SHELF LIFE:	Minimum 24 months in unopened manufacturer's packaging
APPLICATION INFORMATION	
ACTIVE	CONTAINS 7 g/kg (6.3 g/L) 3-Iodo-2-propynyl butylcarbamate (IPBC), 3 g/kg (2.7 g/L) Tebuconazole 0.6 g/kg (0.5 g/L) Permethrin
DENSITY	0.86 @ 20°C
FLASHPOINT	64°C
VOC CONTENT	<700 g/l (Cat. A/f): 700 g/l (2010)
APPLICATION RATE:	180ml/m² 1L per 5.55m ²
APPLICATION METHOD:	Non-Professional/Professional – Brush or roller suitable for solvent-borne products Professional/Industrial – Dipping or Spraying in special facilities
APPLICATION TEMPERATURE:	+10°C to +30°C
DRYING TIME:	12-24 hr
OVERCOAT:	After at least 24hrs
UK AUTHORISATION	HSE 10229
ROI AUTHORISATION	PCS 98549

DIRECTIONS FOR USE

PREPARATION

Wood should be clean, dry and free from wood dust, paint, varnish and other contaminants which may prevent penetration. If necessary grey or deteriorated wood should be sanded down to a clean, sound surface. For Outdoor Use Only. Do not apply in damp conditions or if rain is imminent.

APPLICATION

Supplied ready for use, do not dilute. Mix well before use. Always check colour in an inconspicuous area or with an off-cut of the same timber.

Apply by suitable roller or brush at a rate of at least 180ml/m² or 1L per 5.5m². For best results apply in 2-3 light coats depending on nature of timber.

Timber may also be dipped for a minimum of 3min.

DRYING

Product is touch dry in 12 hours depending on wood and ambient conditions.

Allow at least 24 hours before overcoating or application of subsequent top coats.

RESTRICTIONS

FOR EXTERIOR USE ONLY. Always ensure thoroughly mixed and that colour is tested before use.

STATUTORY CONDITIONS OF APPROVAL RELATING TO USE :

FOR USE ONLY AS A WOOD PRESERVATIVE. Apply by brush or roller at a rate of 180ml/m² (1L per 5.5 m²) Users must comply in full with all their legal responsibilities under The Control of Pesticide Regulations 1986 (as amended), including complying with all conditions of approval. This product is approved under The Control of Pesticides Regulations 1986 (as amended) for use as directed. READ ALL PRECAUTIONS BEFORE USE

PRECAUTIONS

To avoid risks to man and the environment, comply with instructions for use. The precautions generally recommended for handling wood protection products should be observed, e.g. wearing of protective clothing, safety goggles and protective gloves (e.g. nitrile rubber gloves). Do not breathe vapours. Use the product and dry the treated wood only in well ventilated areas. Avoid contact with skin and eyes. After contact with skin, take off immediately all contaminated clothing and wash immediately with plenty of soap and water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed seek medical advice and show container or label. When using do not eat, drink or smoke. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Wood preservatives contain biocidal active ingredients to protect wood against pests. They must be applied according to the instructions for use and only in those cases where protective measures are necessary and where they pose no practical risk to man. They should generally not be used in living or recreational areas. They must to be applied to wood which is likely to come in to prolonged contact with the skin or to wood which comes into direct contact with food and feedstuffs.

QUALITY

This product is manufactured in a plant controlled under an integrated management system third party certified to BS EN ISO 9001.

Use biocides safely. Always read the label and product information before use.